

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ALSAN RS 222 PRIMER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesion promoting primer

1.3. Details of the supplier of the safety data sheet

SOPREMA INC
310 Quadral Drive
Wadsworth, OH 44281 - USA
Tel: 800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) VR2 4H3
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport, MS 39507
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (acct # CCN20515); 24/7. CANUTEC 1-613-996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS US)

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Acute 3	H402

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS02

GHS07

Signal word (GHS US) : Danger

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US)	: H225 - Highly flammable liquid and vapor H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H335 - May cause respiratory irritation H402 - Harmful to aquatic life
Precautionary statements (GHS US)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective gloves, protective clothing. P302+P352 - If on skin: Wash with plenty of water. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 - Call a poison center or doctor if you feel unwell. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P363 - Wash contaminated clothing before reuse. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Methyl methacrylate	(CAS-No.) 80-62-6	15 – 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Acrylated resin	(CAS-No.) Proprietary	10 – 30	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2-Ethylhexyl acrylate	(CAS-No.) 103-11-7	7 – 13	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
4-Methoxyphenol	(CAS-No.) 150-76-5	0.1 – 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Hydroxyethyl acrylate	(CAS-No.) 818-61-1	0.1 – 1	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First Aid measures

4.1. Description of first aid measures

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Carbon dioxide. Dry powder. Water spray.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: Product is not explosive.
Reactivity	: No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Precautionary measures fire	: Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Do not dispose of fire-fighting water in the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.
Other information	: Under fire conditions closed containers may rupture or explode.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Ventilate area. Keep upwind. Remove all sources of ignition. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.

Methods for cleaning up : Use only non-sparking tools. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store in a dry, cool and well-ventilated place.

Incompatible materials : Sources of ignition, direct sunlight. Strong acids or strong bases.

Heat and ignition sources : Avoid ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl methacrylate (80-62-6)		
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL [ppm]	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL TWA [1]	410 mg/m ³
OSHA	OSHA PEL TWA [2]	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	1000 ppm
NIOSH	NIOSH REL TWA	410 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
2-Ethylhexyl acrylate (103-11-7)		
ACGIH	Remark (ACGIH)	OELs not established

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Ethylhexyl acrylate (103-11-7)		
OSHA	Remark (OSHA)	OELs not established
2-Hydroxyethyl acrylate (818-61-1)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
4-Methoxyphenol (150-76-5)		
ACGIH	ACGIH OEL TWA	5 mg/m ³
ACGIH	Remark (ACGIH)	TLV® Basis: Eye irr; skin dam
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL TWA [1]	5 mg/m ³
NIOSH	NIOSH REL TWA	5 mg/m ³
acrylated resin		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.
- Environmental exposure controls : Avoid release to the environment. Dispose of rinse water in accordance with local and national regulations.

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing.

- Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.
- Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
- Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
- Respiratory protection : Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapour, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Off-white
- Odor : Characteristic
- Odor threshold : No data available
- pH : No data available

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 2 °C (35.6 degrees Fahrenheit)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.04 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 1500 cP
Explosive limits	: No data available
Explosive properties	: None known
Oxidizing properties	: No data available

9.2. Other information

VOC content : < 5 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Open flames and extremely high or low temperatures

10.5. Incompatible materials

Strong acids and strong bases

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. If decomposition does occur, flammable gases, fumes, carbon monoxide and carbon dioxide may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Methyl methacrylate (80-62-6)	
LD50 oral rat	7872 mg/kg
LD50 dermal rabbit	> 5 g/kg
LC50 Inhalation - Rat	29.8 mg/l/4h

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl methacrylate (80-62-6)	
LC50 Inhalation - Rat [ppm]	4632 ppm/4h
2-Ethylhexyl acrylate (103-11-7)	
LD50 oral rat	4435 mg/kg
LD50 dermal rabbit	7522 mg/kg
LC50 Inhalation - Rat	> 1.19 mg/l (Exposure time: 8 h Source: ECHA_API)
2-Hydroxyethyl acrylate (818-61-1)	
LD50 oral rat	548 mg/kg
LD50 dermal rat	154 mg/kg
4-Methoxyphenol (150-76-5)	
LD50 oral rat	1600 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Ethylhexyl acrylate (103-11-7)	
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Symptoms/effects	: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology – general : Harmful to aquatic life.

Methyl methacrylate (80-62-6)	
LC50 - Fish [1]	243 – 275 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	69 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	125.5 – 190.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

2-Ethylhexyl acrylate (103-11-7)	
LC50 - Fish [1]	1.81 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
EC50 - Crustacea [1]	17.45 mg/l (Exposure time: 48 h - Species: Daphnia magna)

4-Methoxyphenol (150-76-5)	
LC50 - Fish [1]	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Methoxyphenol (150-76-5)	
EC50 - Crustacea [1]	> 27 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)
ErC50 algae	54.7 mg/l Source: EHCA

12.2. Persistence and degradability

ALSAN RS 222 PRIMER	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

ALSAN RS 222 PRIMER	
Bioaccumulative potential	No information available.

12.4. Mobility in soil

ALSAN RS 222 PRIMER	
Ecology – soil	No data available.

12.5. Other adverse effects

Other adverse effects	: No data available.
Effect on the ozone layer	: No known effect on the ozone layer
Effect on global warming	: No additional information available
Other information	: No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in accordance with local and regional regulations.
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without a permit.
Sewage disposal recommendations	: Avoid direct discharge into drains.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)	: UN1263 Paint, 3, II
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

ALSAN RS 222 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Transport by sea (IMDG)

Transport document description (IMDG)	: UN 1263 PAINT, 3, II
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 5 L

Air transport (IATA)

Transport document description (IATA)	: UN 1263 Paint, 3, II
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

ALSAN RS 222 PRIMER

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Respiratory or skin sensitization
-------------------------------------	--

Methyl methacrylate (80-62-6)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to 2-Ethylhexyl acrylate, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
2-Ethylhexyl acrylate (103-11-7)	X					
Toluene (108-88-3)		X				7000 µg/day

ALSAN RS 222 PRIMER

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Titanium dioxide (13463-67-7)	X				Not available	
Carbon black (1333-86-4)	X					

Component	State or local regulations
Methyl methacrylate (80-62-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
2-Ethylhexyl acrylate (103-11-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
4-Methoxyphenol (150-76-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
2-Hydroxyethyl acrylate (818-61-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Titanium dioxide (13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Toluene (108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Carbon black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Iron oxide (Fe2O3) (1309-37-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Chromium(III) oxide (1308-38-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
Petroleum distillates (naphtha) (8002-05-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

- Other Information : Author: WJS
- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Revision 2.0: Updated SDS.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.