

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 08/11/2023 Revision Date: 8/11/2023 Supersedes: 2/14/2019 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : ALSAN RS DETAILER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

: Micro-fiber enhanced rapid-curing polymethyl methacrylate flashing paste

1.3. Details of the supplier of the safety data sheet

SOPREMA INC 310 Quadral Drive Wadsworth, OH 44281 - USA Tel: 800-356-3521

Distributors: SOPREMA Canada 1675 Haggerty Street Drummondville (Quebec) J2C 5P7 Tel: 1-819-478-8163

SOPREMA Canada 44955 Yale Road West Chilliwack (BC) VR2 4H3 Tel: 1-604-793-7100

SOPREMA USA 12251 Seaway Road Gulfport, MS 39507 Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number

: CHEMTREC: 1-800-424-9300 (acct # CCN20515); 24/7. CANUTEC 1-613-996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS US)

 Flam. Liq. 2
 H225

 Skin Irrit. 2
 H315

 Skin Sens. 1
 H317

 Carc. 1A
 H350

 STOT SE 1
 H370

 STOT SE 3
 H335

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US)	 H225 - Highly flammable liquid and vapor H315 - Causes skin irritation H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation H350 - May cause cancer H370 - Causes damage to organs
Precautionary statements (GHS US)	 P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe vapors, spray, mist, fume. P264 - Wash hands, forearms and face, clothing thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear eye protection, face protection, protective clothing, protective gloves. P302+P352 - If on skin: (Vash with plenty of water. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P303+P313 - If skin irritation or rash occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use media other than water to extinguish.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Silica: Crystalline, quartz	(CAS-No.) 14808-60-7	15 – 40	Carc. 1A, H350 STOT RE 1, H372
Methyl methacrylate	(CAS-No.) 80-62-6	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-Ethylhexyl acrylate	(CAS-No.) 103-11-7	7 – 13	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
4-Morpholinecarboxaldehyde	(CAS-No.) 4394-85-8	0.1 – 1	Skin Sens. 1, H317
Poly(oxy-1,2-ethanediyl), .alpha(1-oxo-2-propenyl)omega[(1-oxo-2-propenyl)oxy]-	(CAS-No.) 26570-48-9	0.1 - 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
9,10-Anthracenedione, 1-hydroxy-4-[(4-methylphenyl)amino]-	(CAS-No.) 81-48-1	0.1 - 1	Skin Sens. 1B, H317

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First Aid measures

	4.1.	Description	of first aid measures
--	------	-------------	-----------------------

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention/advice.
First-aid measures after eye contact	 IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately if pain, blinking or redness persists. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/effects	: Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer. Causes damage to organs.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May cause an allergic skin reaction. May cause cancer. Causes damage to organs.
4.3. Indication of any immediate medical	attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Foam. Dry powder. Dry chemical. Alcohol-resistant foam.	
Unsuitable extinguishing media	: None known.	
5.2. Special hazards arising from the sub	ostance or mixture	
Fire hazard Explosion hazard Reactivity	 Product is flammable. Product is not explosive. The product is non-reactive under normal conditions of use, storage and transport. 	
5.3. Advice for firefighters		
Firefighting instructions	: Use cold water spray to cool fire-exposed containers to minimize risk of rupture. Isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Protection during firefighting	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.	

SECTI	ON 6: Accidental release measu	Jres
6.1.	Personal precautions, protective equi	pment and emergency procedures
Genera	I measures	: Ventilate area. Evacuate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.
6.1.1.	For non-emergency personnel	
Protect	ive equipment	: Wear Protective equipment as described in Section 8.
Emerge	ency procedures	: Evacuate unnecessary personnel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2.	For emergency responders	
Prote	ctive equipment	: For further information refer to section 8: "Exposure controls/personal protection".
6.2.	Environmental precautions	
Notify a	authorities if product enters sewers or p	ublic waters. Prevent entry to sewers and public waters. Avoid release to the environment.
6.3.	Methods and material for contain	ment and cleaning up
For co	ontainment	: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.
Metho	ods for cleaning up	: Vacuum or sweep into container for reuse or disposal. Soak up with inert material. Sweep up material and place in an appropriate chemical waste container for disposal. Do not discharge to sewers or waterways.
6.4.	Reference to other sections	

No additional information available

SECTION 7: Handling and storage		
7.1. Precautions for safe h	andling	
Precautions for safe handling	: Wear personal protective equipment. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with skin and eyes. Avoid ingestion. Avoid inhaling fumes or vapors.	
7.2. Conditions for safe sto	prage, including any incompatibilities	
Storage conditions	: Store in a well-ventilated place. Keep container tightly closed.	

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Silica: Crystalline, quartz (14808-60-7)		
ACGIH	ACGIH OEL TWA	0.025 mg/m ³ (respirable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL TWA [1]	50 μg/m ³ (respirable fraction) (source: 29 CFR § 1910.1053)
OSHA	OSHA PEL TWA [2]	Where 1910.1053 is not in force, use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m ³ / (%SiO2+2)) for mg/m ³ (source: Table Z-3)
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
IDLH	IDLH	50 mg/m ³ (respirable dust)
NIOSH	NIOSH REL TWA	0.05 mg/m ³ (respirable dust)

2-Ethylhexyl acrylate (103-11-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
4-Morpholinecarboxaldehyde (4394-85-8)		
ACGIH Remark (ACGIH) OELs not established		OELs not established

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Morpholinecarboxaldehyde (4394-85-8)		
OSHA	Remark (OSHA)	OELs not established
Methyl methacryl	ate (80-62-6)	
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL [ppm]	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL TWA [1]	410 mg/m ³
OSHA	OSHA PEL TWA [2]	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	1000 ppm
NIOSH	NIOSH REL TWA	410 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
9,10-Anthracened	lione, 1-hydroxy-4-[(4-methylphenyl)amino	·]- (81-48-1)
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Poly(oxy-1,2-etha	nediyl), .alpha(1-oxo-2-propenyl)omega	[(1-oxo-2-propenyl)oxy]- (26570-48-9)
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing.

Hand protection

Eye protection

Skin and body protection Respiratory protection

- : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.
- : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
- : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
- : Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapour, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical p	properties
9.1. Information on basic physical and ch	nemical properties
Physical state	: Liquid/paste
Color	: Gray
Odor	: Characteristic
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: ≈ 101 °C (214°F)
Flash point	: < 22 °C (72°F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 9000 cP
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
0.2. Other information	
N00 / /	

VOC content

: < 10 g/l

SECT	ON 10: Stability and reactivity		
10.1.	Reactivity		
The product is non-reactive under normal conditions of use, storage and transport.			
10.2.	Chemical stability		
Stable under normal conditions of use.			
10.3.	Possibility of hazardous reactions		
No addit	ional information available.		
10.4.	Conditions to avoid		
No addit	ional information available.		
10.5.	Incompatible materials		
No addit	ional information available.		
10.6.	Hazardous decomposition products		

No additional information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquita taxiaity (aral)	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
2-Ethylhexyl acrylate (103-11-7)	
LD50 oral rat	4435 mg/kg
LD50 dermal rabbit	7522 mg/kg
LC50 Inhalation - Rat	> 1.19 mg/l (Exposure time: 8 h Source: ECHA_API)
4-Morpholinecarboxaldehyde (4394-85-8)	
LD50 oral rat	6500 μl/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 18400 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 5.319 mg/l/4h
Methyl methacrylate (80-62-6)	
LD50 oral rat	7872 mg/kg
LD50 dermal rabbit	> 5 g/kg
LC50 Inhalation - Rat	29.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4632 ppm/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen	Yes
list	
2-Ethylhexyl acrylate (103-11-7)	-
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	
	: Not classified
STOT-single exposure	: Not classified : May cause respiratory irritation.
STOT-single exposure STOT-repeated exposure	: May cause respiratory irritation.
STOT-single exposure	May cause respiratory irritation.Not classified
STOT-single exposure STOT-repeated exposure Aspiration hazard	 May cause respiratory irritation. Not classified Not classified ≈ 9000 cP Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May
STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, dynamic Symptoms/effects	 May cause respiratory irritation. Not classified Not classified ≈ 9000 cP Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer. Causes damage to organs.
STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, dynamic Symptoms/effects Symptoms/effects after inhalation	 May cause respiratory irritation. Not classified Not classified ≈ 9000 cP Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer. Causes damage to organs. May cause respiratory irritation.
STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, dynamic Symptoms/effects	 May cause respiratory irritation. Not classified Not classified ≈ 9000 cP Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer. Causes damage to organs. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction.
STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, dynamic Symptoms/effects Symptoms/effects after inhalation Symptoms/effects after skin contact	 May cause respiratory irritation. Not classified Not classified ≈ 9000 cP Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer. Causes damage to organs. May cause respiratory irritation.

SECTI	ON 12: Ecological information	
12.1.	Toxicity	

No additional information available

12.2. Persistence and degradability

No additional information available

SECTION 14: Transport information

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3.	Bioaccumulative potential
No addi	tional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects
No addi	tional information available

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without a permit.			
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.			

Department of Transportation (DOT)				
In accordance with DOT				
Transport document description (DOT) UN-No.(DOT) Proper Shipping Name (DOT) Class (DOT) Packing group (DOT) Hazard labels (DOT)	 UN1263 Paint, 3, II UN1263 Paint 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 II - Medium Danger 3 - Flammable liquid 			
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5L			
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L			
DOT Vessel Stowage Location	B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and of passenger vessel carrying a number of passengers limited to not more than the larger passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On decl on passenger vessels in which the number of passengers specified in paragraph (k)(2 this section is exceeded.	r of 25 k only''		
Emergency Response Guide (ERG) Number	: 128			
Other information	: No supplementary information available.			
Transport by sea (IMDG)				
Transport document description (IMDG)	: UN 1263 PAINT, 3, II			
UN-No. (IMDG)	: 1263			
Proper Shipping Name (IMDG)	: PAINT			
Class (IMDG)	: 3 - Flammable liquids			
Packing group (IMDG)	: II - substances presenting medium danger			
Limited quantities (IMDG)	: 5 L			
Air transport (IATA)				
Transport document description (IATA) UN-No. (IATA)	: UN 1263 Paint, 3, II : 1263			
08/11/2023	ALSAN RS DETAILER	8/11		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium danger

ECTION 15: Regulatory informa		
ALSAN RS DETAILER		
	e listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Specific target organ toxicity (single or repeated exposure)	
Propylene glycol monomethyl ether ac	etate (108-65-6)	
EPA TSCA Regulatory Flag	P - P - indicates a commenced Premanufacture Notice (PMN) substance.	
4-Morpholinecarboxaldehyde (4394-85	-8)	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.	
Poly(oxy-1,2-ethanediyl), .alpha(1-ox	o-2-propenyl)omega[(1-oxo-2-propenyl)oxy]- (26570-48-9)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	

15.2. International regulations

No additional information available

15.3. US State regulations

MARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Titanium dioxide (13463-67-7)	Х				Not available	
Benzene (71-43-2)	Х	X	x		6.4 μg/day (oral); 13 μg/day (inhalation)	24 μg/day (oral); 49 μg/day (inhalation)
Toluene (108-88-3)		Х				7000 µg/day
Cumene (98-82-8)	Х					
Ethylbenzene (100-41- 4)	х				54 μg/day (inhalation); 41 μg/day (oral)	
Carbon black (1333- 86-4)	Х					
Silica: Crystalline, quartz (14808-60-7)	Х					
Diisodecyl phthalate (26761-40-0)		Х			Not available	2200 µg/day

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations		
Titanium dioxide (13463-67-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		
Xylene (1330-20-7)	U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List		
Benzene (71-43-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		
n-Butyl acetate (123-86-4) U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) I			
Toluene (108-88-3)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		
Cumene (98-82-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
Ethylbenzene (100-41-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		
Carbon black (1333-86-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
4-Methoxyphenol (150-76-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List		
Silica: Crystalline, quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		
Iron oxide (Fe2O3) (1309-37-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List		
2,6-Di-tert-butyl-p-cresol (128-37-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List		
Methyl methacrylate (80-62-6)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
2-Ethylhexyl acrylate (103-11-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List		
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List		

SECTION 16: Other information	
Other information	: Author: SS.
NFPA health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS Hazard Rating	
Health	: 3
Health	* - Chronic (long-term) health effects may result from repeated overexposure
Flammability	: 2
Physical	: 0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.