

# SOPRALASTIC®

## 124 ALU

SOPRALASTIC® 124 ALU  
PRODUCT # 30130

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

SOPRALASTIC 124 ALU is a high performance proprietary elastomeric bitumen waterproofing coating with aluminum leafing pigmentation used for revitalizing and protecting waterproofing membranes. SOPRALASTIC 124 ALU may also be used to protect surfaces of sanded membranes and SOPRALASTIC 123 against UV rays.

### STORAGE

Shelf life: Up to 36 months in original sealed containers. Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc. SOPRALASTIC 124 ALU is a highly flammable product. Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with skin. In closed areas, ventilate carefully using mechanical means if necessary. Do not pour residues in drains.

### APPLICATION

SOPRALASTIC 124 ALU is applied with a brush, roller or airless sprayer. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods.



#### QUICK FACTS

#### QUANTITY (gal)

4.76  
(18.0 L)

#### PRODUCT PROPERTIES

Specific gravity at 20°C (68°F)	1.20 kg/L
Color	Aluminum
Solids by weight	64 %
Resistance to frost	Good
Resistance to UV light	Excellent
Drying time	24 hours
Coverage*	1.25 - 1.5 gal/ft <sup>2</sup> per coat

\*If desired, multiple coat application is acceptable for desired thickness. Allow product to dry before additional coatings are applied.



**SOPREMA®**

[www.soprema.us](http://www.soprema.us)  
310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10084 - REV. 240607