


# SOPRAFLASH® UN

Uncured Neoprene Flashing



APPLICATIONS

WATERPROOFING

## DESCRIPTION:

**SOPRAFLASH UN** is a 60-mil heavy-duty uncured neoprene flashing used in conjunction with COLPHENE H and COLPHENE H-EV.

## BASIC USES:

Used to detail horizontal to vertical transitions, penetrations, joints, and other irregular surfaces.

## PACKAGING:

6" x 100' (Product #: W310)

12" x 100' (Product #: W311)

18" x 100' (Product #: W312)

36" x 100' (Product #: W313)

## LIMITATION:

- Do not apply solvents or solvent based products.
- Do not apply to contaminated, wet, or damp surfaces.

## APPLICATION:

Refer to the **COLPHENE H-EV** or **COLPHENE H** application guidelines for complete details.

## WARRANTY:

Please refer to [www.SOPREMA.us](http://www.SOPREMA.us) for the SOPREMA Standard Warranty, Form 115, or contact SOPREMA at 800.356.3521 for more information.

PROPERTY		TEST METHOD
Thickness, mils (mm)	60 (1.5)	ASTM D5147

PROPERTY	VALUE	TEST METHOD
Tensile strength, psi	1484	ASTM D412
Ultimate elongation, %	267	ASTM D412
Tear resistance, lbf/in	171	ASTM D824
Brittleness point @ -40°F	No breaks	ASTM D2137

\* Data is represented by average values, unless noted otherwise.

