


SOPRAFLASH® R

Reinforcement Fabric



APPLICATIONS

WATERPROOFING

PRODUCT DATA SHEET PD10115 REV.005721

DESCRIPTION:

SOPRAFLASH R is a lightweight, thermally bonded spun laid polyester/nylon composite mat.

SOPRAFLASH R is used as a reinforcement in COLPHENE H and COLPHENE H-EV hot rubberized asphalt liquid membrane systems.

BASIC USES:

Used as a reinforcement for COLPHENE H-EV and COLPHENE H.

PACKAGING:

36" X 180' (Product #: W301)

COVERAGE RATE:

508 square feet per roll

COLOR:

White

LIMITATION:

- Do not apply solvents or solvent based products.
- Do not apply to contaminated, wet, or damp surfaces.

APPLICATION:

Refer to the **COLPHENE H-EV** or **COLPHENE H** application guidelines for complete details.

WARRANTY:

Please refer to www.SOPREMA.us for the SOPREMA Standard Warranty, Form 115, or contact SOPREMA at 800.356.3521 for more information.

WEIGHT:

8.25 lbs. per roll

PROPERTY		TEST METHOD
Thickness, mils (mm)	18 (0.45)	ASTM D5147

PROPERTY	MD	XMD	TEST METHOD
Breaking strength, n/s cm (lb/2in)	242.6 (55.2)	192.6 (44)	ISO 9073-3
Elongation at break, (%)	37.5	49.4	ISO 9073-3
Mat weight, oz per sq. yd. (g/m ²)	2.2 (75)		-
Tensile strength, lbf•in (N)	78 (0.009)		ASTM D5034
Tear strength, lb	23.8		ASTM D1117
Puncture resistance, lb	31		ASTM D4930

* Data is represented by average values, unless noted otherwise.

