

ALSAN® RS CLEANER

Solvent-Based Cleaner



APPLICATIONS

ROOFING

WATERPROOFING

PRODUCT DATA SHEET PD10247 - REV 230817

PRODUCT NUMBERS:

- L-RS1CL - 1 gal (3.7 L) Pail
- L-RS007 - 5 gal (18.9 L) Pail

DESCRIPTION & FEATURES:

ALSAN RS CLEANER is a solvent-based solution specially formulated to clean and reactivate fully cured, in-place ALSAN RS membranes. **ALSAN RS CLEANER** is also ideal for cleaning tools and for preparing metal and plastic substrates for application of ALSAN RS resin or ALSAN TRAFIK RS components.

APPLICATION:

Apply **ALSAN RS CLEANER** using a lint free cloth. Thoroughly wipe down the surface membrane and allow the area to dry for approximately 20 minutes. Once clean, follow up with application of RS component within 60-minutes.

Refer to the ALSAN RS Roofing or ALSAN TRAFIK RS Waterproofing Technical Manuals for additional application guidelines.

STORAGE:

Store containers away from excessive heat and sources of ignition. Containers should be kept in a cool, dry indoor environment at temperatures between 55 - 80 °F (13 - 27°C). Avoid prolonged rooftop storage or direct sunlight. PROTECT FROM FREEZING. Approximate shelf life is 12 months from date of shipment when properly stored, sealed and unmixed.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

TECHNICAL INFORMATION & TESTING:

PHYSICAL PROPERTIES*		
PROPERTY	VALUE	ASTM TEST METHOD
Technology	Solvent	-
Color	Clear	-
Flash point, °F (°C)	6 (-14)	D93
Dry time @ 68°F (20°C), min**	20	-
Next coat @ 68°F (20°C), min**	60	-
Ambient temperature, °F (°C)	40 - 95 (4.4 - 35)	-
Shelf life, months	12	-
VOC content, g/L	< 5	EPA Method 24

* Data is represented by average values, unless noted otherwise.

** All working and cure times are approximate and may vary upon wind, humidity and ambient/surface temperatures.

