


ALSAN® RS VINYL CHIPS

Pigmented Acrylic Chips



APPLICATIONS

ROOFING

WATERPROOFING

PRODUCT DATA SHEET PD10361 - REV 230828

PRODUCT NUMBERS:

- L-A156 - 40 lb Bag

DESCRIPTION & FEATURES:

ALSAN RS VINYL CHIPS are solid, chemically inert, pigmented acrylic chips used to create decorative aesthetic finishes for ALSAN RS and ALSAN TRAFIK RS applications.

ALSAN RS VINYL CHIPS are available in 1/4, 1/8 and 1/16 inch flakes a variety of blends and colors.

MIXING:

Use care when handling the vinyl chips, especially while in the bags. Rough handling or throwing the bags around will break chips and create small particles. These small particles will change the appearance of the finish. For best results, transfer the chips to a clean five gallon pail for distribution onto the coating. Using your hands, gently break apart any clumps of chips. Avoid transferring the fine particles of broken chips from the bag or box into the pail.

APPLICATION:

ALSAN RS Vinyl Chips are broadcast into ALSAN RS 285 CF or ALSAN TRAFIK RS 787 CF and then top coated with the clear ALSAN TRAFIK RS 781 CL to lock them in.

Vertical and horizontal surfaces should be cast separately, applying vertical surfaces first followed by deck areas using appropriate protection and masking. On vertical surfaces, cast aggregate into the wet resin with a perpendicular hand motion.

Once the substrate is dry and ready for the top coat you will need to remove any color flakes that did not adhere. The easiest way to do this is to sweep the substrate with a stiff bristle push broom followed by vacuuming or using a leaf blower to remove any loose chips. Apply ALSAN TRAFIK RS 781 CL according to published specifications.

Refer to the ALSAN RS Roofing or ALSAN TRAFIK RS Waterproofing Technical Manuals for additional application guidelines.

STORAGE:

Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.


WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.



ALSAN® RS VINYL CHIPS

Pigmented Acrylic Chips



PRODUCT DATA SHEET PD10361 - REV 230828



APPLICATIONS

ROOFING

WATERPROOFING

FLAKE DIMENSIONS:



1/4 in



1/8 in



1/16 in

STANDARD COLORS:¹



SHORELINE




TAN BLEND



GENEVA



DOMINO




GRANITE BLEND



NORDIC GREEN



SNOWFALL




BLUE BLEND


SPECIAL COLORS:^{1,2}



SAND BLEND




PAINTTAIL



BROWN BLEND



OUTBACK



CREEKBED




RANDOR HUNT



PRETO



NIGHT FALL



GUNFLINT



BLAST STONE



SCHIST STONE



PUMICE STONE



OBSIDIAN STONE



GARNET STONE

¹ Sample photos are shown in 1/4 in format, but are also available in 1/8 in and 1/16 in format. Each format is randomly shaped and sized within a standardized range.

² Special colors are not kept in stock, please allow additional time before receipt.

Color swatches are for representation only and a test patch should be applied to verify a color match. Physical color samples are available upon request.