

ALSAN® COATING BUTYL FLEECE TAPE

Self-Adhesive, Fleece-Faced Reinforcing Tape



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10375 - REV 230626

PRODUCT NUMBERS:

- L-SILFT4 - 4 in x 65.5 ft (10 cm x 20 m) - Roll

DESCRIPTION & FEATURES:

ALSAN COATING BUTYL FLEECE TAPE contains a butyl rubber compound with a polyester fleece face used where required or recommended as reinforcement to enhance tensile strength, tear resistance, elongation and performance of ALSAN Coating applications. ALSAN Coating Butyl Fleece Tape is typically used to treat laps, joints, seams flashings and repairs on metal, single ply and smooth asphalt based roof systems.

APPLICATION:

After the surface has been adequately prepared, cut **ALSAN COATING BUTYL FLEECE TAPE** to the desired length. Remove the release liner and position the tape over the area. Firmly press the tape into place with a hand or roller, ensuring adhesion to the roof surface. Always roll from the center towards the outside to remove any air pockets. Do not stretch tape during application. Edges must be free of any fishmouths. ALSAN coating must be applied over the tape within the same day.

Refer to the SOPREMA Roof Coatings Technical Manual for complete application guidelines.

STORAGE:

Store rolls in an upright position to avoid deforming rolls. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Approximate shelf life is 24 months from date of manufacture when properly stored.

LIMITATIONS

SOPREMA advises that adhesion/peel tests be performed before application to ensure adequate bond can be achieved. For best results, ambient and surface temperatures must be between 40 - 95°F (4.4 - 35°C). Do not attempt application if ice, snow, moisture, or dew are present or expected within 24 hours of application.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.



ALSAN® COATING BUTYL FLEECE TAPE

Self-Adhesive, Fleece-Faced Reinforcing Tape



APPLICATIONS

ROOFING

TECHNICAL INFORMATION & TESTING:

DIMENSION & MASS	
PROPERTY	VALUE
Material	Butyl rubber compound with a polyester fleece face
Length , ft (m)	65.5 (20)
Width , ft (cm)	4 (10)
Thickness , mil (mm)	25 (0.64)
Coverage , ft ² (m ²)	21.8 (2.02)
Weight , lb (kg)	6 (2.72)

PHYSICAL PROPERTIES	
PROPERTY	VALUE
Material	Butyl rubber compound with a polyester fleece face
Color	Grey backing with white face
Application temperature , °F (°C)	40 to 105 (4.4 to 40.5)
Service temperature , °F (°C)	-40 to 194 (-40 to 90)
Shelf life , months	24

Data is represented by typical values, unless noted otherwise.