

ALSAN® RS CATALYST POWDER

Resin Curing Agent



APPLICATIONS

ROOFING

WATERPROOFING

PRODUCT DATA SHEET PDS10324 - REV 240109

PRODUCT NUMBERS:

- L-RS003 - **3.5 oz (0.1 kg) Packet**
- L-RS006 - **55lb (25 kg) Box**
- L-RS111 - **42 oz (1.2 kg) Bottle**

DESCRIPTION & FEATURES:

ALSAN RS CATALYST is a reactive agent used to induce curing of ALSAN RS or ALSAN TRAFIK RS resin products. ALSAN RS Catalyst is available in 0.1 kg resealable packets (measuring scoop needed), 1.2 kg plastic bottles with measuring cap and 25 kg bulk boxes.

APPLICATION:

Wear proper PPE (personal protective equipment) when handling this product and avoid contact with skin and eyes. Using a slow-speed (200-400 rpm) mechanical agitator, thoroughly mix the entire container of resin for two minutes before use. Only catalyze the amount of material that can be used within 10 -15 minutes. The amount of catalyst required is determined by resin weight and ambient temperature. See resin product data sheets for specific catalyst amounts. Add the pre-measured catalyst to the resin, stir for two minutes and apply to substrate.

For complete catalyst dosage amounts refer to specific ALSAN RS and ALSAN TRAFIK RS product data sheets for specifications and mixing instructions.

STORAGE:

Storage temperature range should be between 55°F (12.8°C) and 86°F (30°C). Store container upright in a clean, dry location and protect from environmental damage, such as extreme heat, direct sunlight and moisture. Store away from reducing agents, strong oxidizers, alkalis, accelerators and pressurized containers. Storage guidelines must be followed to avoid possible exothermic self-accelerating decomposition/ fire. Shelf life is 12 months from date of shipment when properly stored and sealed.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

