

# ALSAN® TRAFIK RS 733 PART A

High-Performance, Rapid-Setting Liquid Resin



APPLICATIONS

WATERPROOFING

PRODUCT DATA SHEET PDS10463A - REV 221214

## PRODUCT NUMBERS:

- 00513770 - **10 kg (9.4 L) Pail (Summer)**
- 00513771 - **10 kg (9.4 L) Pail (Winter)**

*Requires the addition of ALSAN RS 733 Part B and ALSAN RS Catalyst.*

## DESCRIPTION & FEATURES:

**ALSAN TRAFIK RS 733 PART A** is a high-performance rapid-setting, polymethyl methacrylate (PMMA) resin.

**ALSAN TRAFIK RS 733 PART A** (resin) is utilized in conjunction with ALSAN TRAFIK RS 733 Part B (filler) to create ALSAN TRAFIK RS 733 Self-Leveling Mortar.

**ALSAN TRAFIK RS 733 PART A** (resin) is available in both a summer and winter formula.

## STORAGE:

Store container in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat, or moisture. Storage temperature range should be between 55°F (12.7°C) and 80°F (26.6°C). Approximate shelf life is 12 months from date of shipment when properly stored, sealed and unmixed.

## APPLICATION:

**ALSAN TRAFIK RS 733 PART A** (resin) is mixed with ALSAN TRAFIK RS 733 Part B (filler) to make ALSAN TRAFIK RS 733 Self-Leveling Mortar. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods.

For complete catalyst dosage amounts and product coverage rates see the ALSAN TRAFIK RS 733 SelfLeveling Mortar PDS.

## TESTING & APPROVALS:

FLORIDA BUILDING CODE

FL13086

## WARRANTY:

For more information refer to [www.SOPREMA.us](http://www.SOPREMA.us) or contact your SOPREMA representative.

