

ALSAN® TRAFIK RS 733 PART B

Part B Aggregate Filler for ALSAN Self-Leveling Mortar



APPLICATIONS

WATERPROOFING

PRODUCT DATA SHEET PD10463A - REV 221128

PRODUCT NUMBERS:

- 00513772 - **23 kg bag packaged in 7-gallon plastic pail for mixing**
Requires the addition of ALSAN RS 733 Part A (Summer or Winter) and ALSAN RS Catalyst.

DESCRIPTION & FEATURES:

ALSAN TRAFIK RS 733 PART B (filler) is utilized in conjunction with ALSAN TRAFIK RS 733 Part A Summer or Winter (resin) to create ALSAN TRAFIK RS 733 Self-Leveling Mortar. It may also be used with ALSAN RS 240 LO to create ALSAN RS 263 LO Self-Leveling Mortar.

STORAGE:

Store container in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat, or moisture. Storage temperature range should be between 55°F (12.7°C) and 80°F (26.6°C). Approximate shelf life is 12 months from date of shipment when properly stored, sealed and unmixed.

APPLICATION:

ALSAN TRAFIK RS 733 PART B (filler) is mixed with ALSAN TRAFIK RS 733 Part A (resin) to make ALSAN TRAFIK RS 733 Self-Leveling Mortar. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods.

For complete catalyst dosage amounts and product coverage rates see the ALSAN TRAFIK RS 733 Self Leveling Mortar PDS.

TESTING & APPROVALS:

FLORIDA BUILDING CODE

FL13086

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

