

SENTINEL® BOOT FLASHING

Pre-Fabricated Conical PVC Pipe Flashing



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10323- REV 240221

PRODUCT NUMBERS:

1 - 6 INCH PIPE DIA — SPLIT

- P610 - 1 - 6 in (2.5 - 15.2 cm) - White
- OP610-G - 1 - 6 in (2.5 - 15.2 cm) - Grey
- OP610-T - 1 - 6 in (2.5 - 15.2 cm) - Tan

1 - 6 INCH PIPE DIA — CLOSED

- P611 - 1 - 6 in (2.5 - 15.2 cm) - White
- P611-G - 1 - 6 in (2.5 - 15.2 cm) - Grey
- OP611-T - 1 - 6 in (2.5 - 15.2 cm) - Tan

6 - 12 INCH PIPE DIA — SPLIT

- P612 - 6 - 12 in (15.2 - 30.5 cm) - White
- OP612-G - 6 - 12 in (15.2 - 30.5 cm) - Grey
- OP612-T - 6 - 12 in (15.2 - 30.5 cm) - Tan

6 - 12 INCH PIPE DIA — CLOSED

- P613 - 6 - 12 in (15.2 - 30.5 cm) - White
- P613-G - 6 - 12 in (15.2 - 30.5 cm) - Grey
- OP613-T - 6 - 12 in (15.2 - 30.5 cm) - Tan

Grey and tan boot flashings are available by special order. Contact customer service for lead times and product availability.

DESCRIPTION & FEATURES:

SENTINEL BOOT FLASHINGS are factory fabricated, cone-shaped boots made using reinforced SENTINEL P150 PVC membrane. Available for traditional or split-pipe applications, **SENTINEL BOOT FLASHINGS** are offered in two sizes to fit either 1 - 6 in or 6 -12 in pipe diameters. Each pipe flashing is shipped with a stainless steel clamping ring.

- Prefabricated flashings not only enhance a roof's aesthetics but add lasting durability to a roof system's long-term performance
- Eliminating the need to customize flashings on site contributes to cleaner installations with less job-site waste
- Prefabricated accessories are fast and easy to install, providing greater job site productivity and reduced labor costs

APPLICATION:



HOT-AIR
WELDING

SENTINEL BOOT FLASHINGS are hot-air welded to the field membrane. Seal the top of the pipe flashing watertight with mastic and a pipe clamp (included).

Contact SOPREMA or refer to published guidelines for additional details and application requirements.

PACKAGING & DIMENSIONS:

PROPERTY	VALUE	
Size (diameter), in (cm)	1-6 (2.5 -15.2)	6-12 (15.2 - 30.5)
Packaging	10/box	
Thickness, mils (mm)	60 (1.5)	

STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

