


SENTINEL® PVC PROFILE BAR

Extruded, Pliable PVC Bar



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10179 - REV 240221

PRODUCT NUMBERS: (L x W x H)

- P650 - **9.8 ft x 1.4 in x 1.2 in**
(**3.0 m x 3.5 cm x 3.1 cm**) - **White**
- P650-G - **9.8 ft x 1.4 in x 1.2 in**
(**3.0 m x 3.5 cm x 3.1 cm**) - **Grey**
- P650-T - **9.8 ft x 1.4 in x 1.2 in**
(**3.0 m x 3.5 cm x 3.1 cm**) - **Tan**

Grey and tan profile bars are available by special order. Contact customer service for lead times and product availability.

DESCRIPTION & FEATURES:

SENTINEL PVC PROFILE BARS are extruded, pliable PVC bars designed to provide SENTINEL PVC and KEE membranes with the appearance of a standing seam metal roof. **SENTINEL PVC PROFILE BARS** are available in white, tan and grey.

APPLICATION:



HOT-AIR
WELDING

SENTINEL PVC PROFILE BARS are installed to the membrane using a hot air welder. The profile bar can be installed on both flat and curved surfaces, and can be applied on any slope. When installing the profile bar, tack weld the bar in place to ensure it is straight prior to heat welding it into place.

Contact SOPREMA or refer to published guidelines for additional details and application requirements.

PACKAGING & DIMENSIONS:

PROPERTY	VALUE
Length , ft (m)	9.8 (3.0)
Width , in (cm)	1.4 (3.5)
Height , in (cm)	1.2 (3.1)
Packaging	10/box
Coverage (per box) , LF (LM)	98 (30)

STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.