


# SENTINEL® T-JOINT PATCHES

Prefabricated T-Joint PVC Membrane



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10178 - REV 240221

## PRODUCT NUMBERS:

- P506 - 4.5 in DIA (11.4 cm) - Rounds (White)
- PP506G - 4.5 in DIA (11.4 cm) - Rounds (Grey)
- P506T - 4.5 in DIA (11.4 cm) - Rounds (Tan)

*Grey and tan T-joint Patches are available by special order.  
Contact customer service for lead times and product availability.*

## DESCRIPTION & FEATURES:

**SENTINEL T-JOINT PATCHES** are made using 60 mil, reinforced SENTINEL P150 PVC membrane cut into a perfect 4.5 in-diameter circle. **SENTINEL T-JOINT PATCHES** are designed to seal seam laps where perimeter and/or header sheets intersect (T-Joints) in SENTINEL PVC systems.

- Provides a more professional and uniform appearance compared to field-fabricated covers
- Offers significant labor savings compared to hand cut flashings

## APPLICATION:



HOT-AIR  
WELDING

**SENTINEL T-JOINT PATCHES** shall be hot-air welded to the membrane at all t-joint intersections. Chamfer the welding seam prior to installing **SENTINEL T-JOINT PATCHES**, using an edging tool or by heating the edge and rolling.

Contact SOPREMA or refer to published guidelines for additional details and application requirements.

## PACKAGING & DIMENSIONS:

PROPERTY	VALUE
<b>Size (diameter)</b> , in (cm)	4.5 (11.4)
<b>Packaging</b>	100/box
<b>Thickness</b> , mils (mm)	60 (1.5)

## STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

## WARRANTY:

For more information refer to [www.SOPREMA.us](http://www.SOPREMA.us) or contact your SOPREMA representative.