



# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 5/18/2015 Revision date: 3/17/2023 Supersedes: 5/18/2015 Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : COPLY Flashing Cement

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Roofing/Waterproofing

#### 1.3. Supplier

SOPREMA, Inc.  
310 Quadral Dr  
Wadsworth, OH 44281  
T 1-800-356-3521

SOPREMA USA  
12251 Seaway Road  
Gulfport (Mississippi)  
39507 UNITED STATES  
Tel: 1-228-701-1900

Distributors:  
SOPREMA Canada  
44955 Yale Road West  
Chilliwack (BC) V2R 4H3 CANADA  
Tel: 1-604-793-7100

SOPREMA Canada  
1675 Haggerty Street  
Drummondville (Quebec) J2C 5P7  
Tel: 1-819-478-8163

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Germ cell mutagenicity Category 1B	H340	May cause genetic defects (Dermal, Inhalation)
Carcinogenicity Category 1B	H350	May cause cancer (Inhalation, Dermal)
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs (central nervous system, eyes, Skin, lungs, liver) through prolonged or repeated exposure (Dermal, Inhalation)

Full text of H statements : see section 16

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor  
H340 - May cause genetic defects (Dermal, Inhalation)  
H350 - May cause cancer (Inhalation, Dermal)  
H372 - Causes damage to organs (central nervous system, eyes, Skin, lungs, liver) through prolonged or repeated exposure (Dermal, Inhalation)

Precautionary statements (GHS US) :

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe fume, gas, vapors.  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P280 - Wear protective gloves, protective clothing.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
asphaltic bitumen, not cut back	CAS-No.: 8052-42-4	50 – 60	Not classified

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
kaolin	CAS-No.: 1332-58-7	15 – 30	Not classified
Stoddard solvent	CAS-No.: 8052-41-3	15 – 25	Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
attapulgite	CAS-No.: 12174-11-7	5 – 10	Not classified
cellulose	CAS-No.: 9004-34-6	3 – 7	Not classified
styrene-ethylene/butene-styrene,block copolymer	-	0.1 – 1	Not classified

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause moderate irritation.
Symptoms/effects after eye contact	: Eye irritation.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Absorb spillage to prevent material-damage. Isolate from fire, if possible, without unnecessary risk. No flames, no sparks. Eliminate all sources of ignition. Remove ignition sources.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Protective clothing. Gloves.
- Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray.
Handling temperature	: < 110 (≤ 100) °F
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: < 43 °C
Heat-ignition	: KEEP SUBSTANCE AWAY FROM: ignition sources.
Information on mixed storage	: No data available.
Storage area	: Meet the legal requirements.
Special rules on packaging	: Keep only in original container. meet the legal requirements. Store in a closed container. correctly labelled.
Packaging materials	: No data available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>COPLY Flashing Cement</b>	
No additional information available	
<b>asphaltic bitumen, not cut back (8052-42-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	0.5 mg/m <sup>3</sup> (Inhalable fraction)
<b>attapulgite (12174-11-7)</b>	
No additional information available	
<b>cellulose (9004-34-6)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Cellulose
ACGIH OEL TWA	10 mg/m <sup>3</sup>

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cellulose (9004-34-6)	
Remark (ACGIH)	NA URT irr
kaolin (1332-58-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Kaolin
ACGIH OEL TWA	2 mg/m <sup>3</sup>
Remark (ACGIH)	Pneumoconiosis
Stoddard solvent (8052-41-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Stoddard solvent
ACGIH OEL TWA [ppm]	100 ppm
Remark (ACGIH)	Eye, skin, & kidney dam;
USA - OSHA - Occupational Exposure Limits	
Local name	Stoddard solvent
OSHA PEL TWA [1]	2900 mg/m <sup>3</sup>
OSHA PEL TWA [2]	500 ppm
styrene-ethylene/butene-styrene,block copolymer	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	3 mg/m <sup>3</sup> (Respirable fraction)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

#### Hand protection:

Wear protective gloves.

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear appropriate mask. Wear respiratory protection.

#### Personal protective equipment symbol(s):



# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: BLACK FIBERED MASTIC.
Color	: Black
Odor	: Petroleum-like odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 300 (≤ 450) °F
Flash point	: 106 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: 0.293 kPa at 20 °C
Relative vapor density at 20 °C	: No data available
Relative density	: 1.02 – 1.12
Density	: ≈ 8.5 (8 – 9) lb/gal
Solubility	: Water: 0 % Organic solvent: ≈ 100 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: ≥ 500 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available.
Oxidizing properties	: No data available.

### 9.2. Other information

VOC content	: < 250 (≤ 250) g/l
Percent Solids	: > 75 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids. Strong bases.

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Lack of data)  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### asphaltic bitumen, not cut back (8052-42-4)

LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 0.094 mg/l (OECD 403: Acute Inhalation Toxicity, 4.5 h, Rat, Male / female, Experimental value, No effect, Inhalation (mixture of vapour and aerosol), 14 day(s))

#### cellulose (9004-34-6)

LD50 oral rat	> 5000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat	> 6 mg/l (4 h, Rat, Inhalation)

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : May cause genetic defects (Dermal, Inhalation).  
Carcinogenicity : May cause cancer (Inhalation, Dermal).  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Causes damage to organs (central nervous system, eyes, Skin, lungs, liver) through prolonged or repeated exposure (Dermal, Inhalation).

#### Stoddard solvent (8052-41-3)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified  
Viscosity, kinematic :  $\geq 500 \text{ mm}^2/\text{s}$   
Likely routes of exposure : Inhalation. Skin and eye contact.  
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.  
Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.  
Symptoms/effects after inhalation : May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.  
Symptoms/effects after skin contact : May cause an allergic skin reaction. May cause moderate irritation.  
Symptoms/effects after eye contact : Eye irritation.  
Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:



# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

cellulose (9004-34-6)	
LC50 - Fish [1]	> 100 mg/l (Pisces)
EC50 - Crustacea [1]	> 100 mg/l (Invertebrata)

#### 12.2. Persistence and degradability

COPLY Flashing Cement	
Persistence and degradability	Not established.
asphaltic bitumen, not cut back (8052-42-4)	
Persistence and degradability	Not readily biodegradable in water.
attapulgite (12174-11-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
cellulose (9004-34-6)	
Persistence and degradability	Biodegradable in water.
kaolin (1332-58-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
styrene-ethylene/butene-styrene,block copolymer	
Persistence and degradability	Biodegradability in soil: no data available.

#### 12.3. Bioaccumulative potential

COPLY Flashing Cement	
Bioaccumulative potential	Not established.
asphaltic bitumen, not cut back (8052-42-4)	
Bioaccumulative potential	No bioaccumulation data available.
attapulgite (12174-11-7)	
Bioaccumulative potential	No bioaccumulation data available.
cellulose (9004-34-6)	
Bioaccumulative potential	Bioaccumulation: not applicable.

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

kaolin (1332-58-7)	
Bioaccumulative potential	No bioaccumulation data available.
Stoddard solvent (8052-41-3)	
Partition coefficient n-octanol/water (Log Pow)	3.16 – 7.06
styrene-ethylene/butene-styrene,block copolymer	
Bioaccumulative potential	No bioaccumulation data available.

### 12.4. Mobility in soil

asphaltic bitumen, not cut back (8052-42-4)	
Ecology - soil	No (test)data on mobility of the substance available.
attapulgite (12174-11-7)	
Ecology - soil	No (test)data on mobility of the substance available.
Stoddard solvent (8052-41-3)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.85 – 6.74 (log Koc)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Flammable vapors may accumulate in the container.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA No : Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated  
UN-No. (TDG) : Not applicable  
UN-No. (IMDG) : Not applicable  
UN-No. (IATA) : Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **TDG**

Transport hazard class(es) (TDG) : Not applicable

### **IMDG**

Transport hazard class(es) (IMDG) : Not applicable

### **IATA**

Transport hazard class(es) (IATA) : Not applicable

### **14.4. Packing group**

Packing group (DOT) : III  
Packing group (TDG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### **14.5. Environmental hazards**

Other information : No supplementary information available.

### **14.6. Special precautions for user**

#### **DOT**

UN-No.(DOT) : Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated

#### **TDG**

No data available

#### **IMDG**

No data available

#### **IATA**

No data available

### **14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## **SECTION 15: Regulatory information**

### **15.1. US Federal regulations**

#### **COPLY Flashing Cement**

Not subject to reporting requirements of the United States SARA Section 313

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
asphaltic bitumen, not cut back	8052-42-4	Present	Active	
attapulgite	12174-11-7	Present	Inactive	
cellulose	9004-34-6	Present	Active	XU
kaolin	1332-58-7	Present	Active	XU
Stoddard solvent	8052-41-3	Present	Active	XU
styrene-ethylene/butene-styrene,block copolymer		Present	Inactive	XU

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

COPLY Flashing Cement	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

attapulgite (12174-11-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
asphaltic bitumen, not cut back(8052-42-4)	U.S. - New Jersey - Right to Know Hazardous Substance List
cellulose(9004-34-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
kaolin(1332-58-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Stoddard solvent(8052-41-3)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/17/2023

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

# COPLY Flashing Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

### Hazard Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II IIIA)
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- Personal protection : p - Gloves

Soprema SDS USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.