

CUT-IN REGLET 1" MIN. DEEP, APPLY APPROVED CAULKING AS REQUIRED.

PREPARE, LEVEL & PATCH SUBSTRATE W/ ALSAN RS PASTE OR ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF SOPREMA ALSAN RS PRIMER & MEMBRANE (TYP.)

SOPREMA ALSAN RS MEMBRANE 2" (5cm) MINIMUM OVERLAP TO PROVIDE CONTINUOUS FLASHING


(1) PLY SOPREMA ALSAN RS MEMBRANE FLASHING EXTEND THRU TO OUTSIDE OF OPENING & OVERLAP 2" (5cm) TO FORM SCUPPER FLASHING

ASSURE FULL SATURATION OF FLEECE & CONTACT W/SUBSTRATE.

SOPREMA ALSAN RS FIELD MEMBRANE

NOTE: METAL OR PVC SCUPPER SLEEVE THRU WALL OPTIONAL (BY OTHERS)

NOTES:  
 1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066		
		TITLE THRU-WALL DRAIN FLASHING		
SCALE	NONE	DWN DMT	CHK MT	APPROVAL DATE 5/30/07
DRAWING NUMBER D-2a-RS				REV 0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.