

SOPREMA ALSAN RS MEMBRANE FLASHING—EXTEND 4” (10cm) MIN. HORIZONTALLY ONTO MODIFIED BITUMEN/BUR MEMBRANE.

SOPREMA ALSAN RS FIELD MEMBRANE TIE-IN A MIN OF 4” (10cm) TO THE RS MEMBRANE FLASHING.

ACCEPTABLE PATCHING MATERIALS TO PROVIDE SMOOTH TRANSITION BETWEEN SUBSTRATE & BUR.


EXISTING MODIFIED BITUMEN CAP SHEET OR BUR MEMBRANE PREPARED CLEANED & PRIMED AS REQUIRED.

4” MIN. (10cm)

4” (10cm) MIN.

PREPARE, LEVEL & PATCH SUBSTRATE W/ ALSAN RS PASTE OR ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF SOPREMA ALSAN RS PRIMER & MEMBRANE (TYP.)

NOTES:  
 1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE WATERPROOFING MEMBRANE TRANSITION TO MODIFIED BITUMEN\BUR MEMBRANE			
SCALE	DWN	CHK	APPROVAL DATE
NONE	TM	MT	2/14/14
DRAWING NUMBER			REV
M-4C-RS			0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.