



EXTEND SURFACE PREP MAX.
1/8" BEYOND LINE OF SOPREMA
ALSAN RS FLASHING & COVER
W/ SOPREMA ALSAN RS RESIN.

POWER TOOL CLEAN TUBE
STEEL PER SSPC-SP3.

SOPREMA ALSAN RS
MEMBRANE SKIRT WRAPPED
AROUND PIPE W/ 2" (5cm)
MIN. OVERLAP

SOPREMA ALSAN RS
FIELD MEMBRANE

SOPREMA ALSAN RS
MEMBRANE COLLAR CUT
INSIDE DIA. SAME SIZE AS
PIPE DIAMETER

EXISTING BUR W/NEW FELT
BASE SHEET (IF REQUIRED)

6" (15cm) MIN.

4" (10cm)

2" (5cm)

EXISTING RIGID INSULATION

VAPOR BARRIER IF EXISTING
TO REMAIN.

VAPOR PERMEABLE
BATT INSULATION FILL

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.



310 QUADRAL DRIVE
WADSWORTH, OHIO 44281
(330) 334-0066

TITLE ONE-WAY MECHANICAL MOISTURE VAPOR RELIEF VENT DETAIL			
SCALE NONE	DWN DMT	CHK MT	APPROVAL DATE 5/30/07
DRAWING NUMBER P-3-RS			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.