

SBL ROOF CEMENT

ELASTOMERIC UTILITY CEMENT

SBL ROOF CEMENT
PRODUCT # A235 (5 Gal)

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

SBL Roof Cement is an asbestos-free, trowel grade mastic for use in approved multi-ply membrane assemblies. It is composed of a proprietary formulation of elastomeric modified bitumen and solvents, creating an easy to apply cement with superior adhesion characteristics. SBL Roof Cement can be used in both wet and dry applications. Ideal for multi-ply SBS, APP and BUR roofing systems, SBL Roof Cement can also be used for repairs on shingle roof assemblies.

STORAGE

Store in original packaging and maintain in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of SBL Roof Cement.

ADVANTAGES

- Compatible with a variety of roofing assemblies
- Apply on dry, damp, or wet substrate
- Ideal for temporary emergency repairs and maintenance
- Perfect for night tie-ins
- Smooth spreadability designed with the contractor in mind
- Superior wet adhesion to granule surfacing
- Enhanced sag resistance versus comparable products

PHYSICAL PROPERTIES

Physical Property	ASTM D4586 - Compliant (Type I, Class II) ASTM D3409 - Compliant
Description	Elastomeric modified bitumen utility roof cement
Application*	Trowel
Packaging	5 gallon pail (18.9 L)
Coverage	8 gal/100 ft ²

*Refer to the SOPREMA SBS Roofing Guide for additional application guidelines



SOPREMA[®]

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10395 - REV. 024520