

# ALSAN<sup>®</sup> RS 210

ALSAN<sup>®</sup> RS 210

PRODUCT #  
L-RS010S

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

ALSAN RS 210 is a high performance, rapid-setting, polymethyl methacrylate (PMMA) resin. ALSAN RS 210 is utilized in conjunction with ALSAN RS 223 Mixing Powder to create ALSAN RS 233 Self Leveling Mortar.

### STORAGE

Always store closed containers in cool, ventilated and dry location away from heat and oxidizing agent. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Approximate shelf life is twelve months from date of manufacture when properly stored sealed and unmixed.

### APPLICATION

ALSAN RS 210 is mixed with ALSAN RS 223 Mixing Powder to make ALSAN RS 233 Self-Leveling Mortar and applied with a notched trowel, or using a masonry float. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods.

Refer to the ALSAN RS 233 Self-Leveling Mortar product data sheet for more information regarding mixing and application.



#### QUICK FACTS

UNIT SIZE  
(kg)

10  
(9.5 L)



**SOPREMA<sup>®</sup>**

[www.soprema.us](http://www.soprema.us)

310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10231- REV. 035016