

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : ALSAN RS 222 Primer
 CAS No : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesion promoting primer

1.3. Details of the supplier of the safety data sheet

Manufacturer:
 SOPREMA INC.
 310 Quadral Dr.
 Wadsworth, OH 44281
 Tel: 1-800-356-3521

Distributors:
 SOPREMA Canada
 1675 Haggerty Street
 Drummondville (Quebec) J2C 5P7
 Tel: 1-819-478-8163

SOPREMA Canada
 44955 Yale Road West
 Chilliwack (BC) V2R 4H3
 CANADA
 Tel: 1-604-793-7100

SOPREMA USA
 12251 Seaway Road
 Gulfport (Mississippi) 39507
 UNITED STATES
 Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flammable liquids Category 2 H225
 Skin corrosion/irritation Category 2 H315
 Skin sensitization Category 1 H317
 Specific target organ toxicity (single exposure) Category 3 H335

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Contains :

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate; 2-ethylhexyl acrylate; 2-hydroxyethyl acrylate, stabilized

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US)	H335 - May cause respiratory irritation : P210 - Keep away from sources of ignition, torches and open flames. - No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust, mist, spray, vapors P264 - Wash hands, forearms and face thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear nitrile gloves P302+P352 - If on skin: Wash with plenty of water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P312 - Call a poison center if you feel unwell P321 - Specific treatment (see a doctor on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P363 - Wash contaminated clothing before reuse P370+P378 - In case of fire: Use ABC-powder, BC-powder, dry sand, foam to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of container in accordance with local, regional or national regulations
-----------------------------------	---

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate	(CAS No) 80-62-6	22 - 41	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-ethylhexyl acrylate	(CAS No) 103-11-7	5 - 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Diisopropanol-p-toluidine	(CAS No) 38668-48-3	0.1 - 1	Acute Tox. 3 (Oral), H301
2-hydroxyethyl acrylate, stabilized	(CAS No) 818-61-1	0.02 - 0.3	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Gently wash with plenty of soap and water. Get medical advice/attention. Specific treatment (see Call a physician immediately on this label). If skin irritation or rash occurs: Wash with plenty of soap and water.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion : No data available.
Symptoms/injuries upon intravenous administration : No effects known.
Chronic symptoms : No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.
Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Tip the container on one side to stop the leakage. Dam up the liquid spill.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Avoid breathing dust, mist, spray, vapors. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage temperature	: 0 - 25 °C
Heat-ignition	: KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ALSAN RS 222 Primer		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; body weight eff; DSEN; RSEN; A4
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; body weight eff; DSEN; RSEN; A4
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
2-ethylhexyl acrylate (103-11-7)		
Not applicable		
Diisopropanol-p-toluidine (38668-48-3)		
Not applicable		
2-hydroxyethyl acrylate, stabilized (818-61-1)		
Not applicable		

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear nitrile gloves protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Respiratory protection not required in normal conditions.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Off-white
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: No data available
Flash point	: ≈ 35.6 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Specific Gravity	: ≈ 1.03
Relative vapor density at 20 °C	: No data available
Density	: ≈ 1.03 g/cm ³
Solubility	: Insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 1500 cP

9.2. Other information

VOC content : < 5 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Diisopropanol-p-toluidine (38668-48-3)	
LD50 oral rat	≈ 25 - 200 mg/kg
ATE US (oral)	25.000 mg/kg body weight
2-hydroxyethyl acrylate, stabilized (818-61-1)	
LD50 oral rat	540 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 1000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	540.000 mg/kg body weight
ATE US (dermal)	300.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
IARC group	3 - Not classifiable

2-ethylhexyl acrylate (103-11-7)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
---	---

Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation.
------------------------------------	--

Symptoms/injuries after skin contact	: Causes skin irritation.
--------------------------------------	---------------------------

Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
-------------------------------------	--

Symptoms/injuries after ingestion	: No data available.
-----------------------------------	----------------------

Symptoms/injuries upon intravenous administration	: No effects known.
---	---------------------

Chronic symptoms	: No effects known.
------------------	---------------------

SECTION 12: Ecological information

12.1. Toxicity

2-hydroxyethyl acrylate, stabilized (818-61-1)	
LC50 fish 1	6.5 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	0.78 mg/l (OECD 202: Daphnia sp. Acute Immobilization Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	6 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

ALSAN RS 222 Primer	
Persistence and degradability	Not established.

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
Persistence and degradability	Not established.

2-ethylhexyl acrylate (103-11-7)	
Persistence and degradability	Not established.

Diisopropanol-p-toluidine (38668-48-3)	
Persistence and degradability	Not established.

2-hydroxyethyl acrylate, stabilized (818-61-1)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

ALSAN RS 222 Primer	
Bioaccumulative potential	Not established.

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
Bioaccumulative potential	Not established.

2-ethylhexyl acrylate (103-11-7)	
Bioaccumulative potential	Not established.

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diisopropanol-p-toluidine (38668-48-3)	
Bioaccumulative potential	Not established.
2-hydroxyethyl acrylate, stabilized (818-61-1)	
Log Pow	-0.17 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

2-hydroxyethyl acrylate, stabilized (818-61-1)	
Surface tension	0.028 N/m (20 °C)
Log Koc	-0.029 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of container in accordance with local, regional or national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

DOT Proper Shipping Name : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons) B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F) TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

UN-No.(IATA)	: 1263
Proper Shipping Name (IATA)	: PAINT
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
CERCLA RQ	1000 lb
2-ethylhexyl acrylate (103-11-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Diisopropanol-p-toluidine (38668-48-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

No additional information available

ALSAN® RS 222 Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)

U.S. - Massachusetts - Right to Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

2-ethylhexyl acrylate (103-11-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 08/22/2019

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H400	Very toxic to aquatic life

SDS US (GHS HazCom 2012)

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.