



SOUNDPROOFING

INSONOFLOOR

SOUNDPROOFING

FLOOR SOUNDPROOFING SYSTEM



INSONOFLOOR is a high density polyethylene membrane coated with small granules of recycled rubber. INSONOFLOOR is specially designed to soundproof laminated floating floors, which can be installed directly on the membrane. This product can also be used with other types of flooring such as hardwood floors or multi-layer engineered wood floors.

BENEFITS

- Superior soundproofing performance
- Rot proof and resists water leaks and humidity
- Molds to the shape of the support
- Tear resistant
- No mechanical fasteners necessary
- Retains its flexibility and does not flatten
- Made from recycled materials
- Provides enhanced comfort



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

PRODUCT CHARACTERISTICS

INSONOFLOOR	
THICKNESS	1/8 in (3.5 mm)
DIMENSIONS	35 in x 34.5 ft (0.89 m x 10.5 m)
COVERAGE	100 ft ² (9.3 m ²)
WEIGHT	43 lbs (19.5 kg)
THERMAL PERFORMANCE (R-VALUE)	0.30

INSTALLATION METHOD

- Unroll the INSONOFLOOR membrane on the floor granule side down.
- Install membranes side by side and overlap the ungranulated edges.
- Seal the side and end laps with construction tape.



If you have any questions about this product or its installation, please contact your SOPREMA representative.

