

# SOPRAMASTIC®

## SBS ELASTIC CEMENT

SOPRAMASTIC®  
SBS ELASTIC CEMENT  
PRODUCT # D35635 (5 GAL)  
D35651 (Tubes)

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

SOPRAMASTIC SBS Elastic Cement is a modified bitumen mastic for use in approved multi-ply membrane and flashing assemblies. SOPRAMASTIC SBS Elastic Cement is composed of a proprietary formulation of elastomeric modified bitumen and solvents. SOPRAMASTIC SBS Elastic Cement may be used as an adhesive for drain leads, pipe flanges, metal gravel stops, and more.

### STORAGE

Store in original packaging and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of SOPRAMASTIC SBS Elastic Cement.

### APPLICATION

SOPRAMASTIC SBS Elastic Cement is applied to the approved area via caulking gun or trowel. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.

### PHYSICAL PROPERTIES

Physical Property	ASTM D4586
Description	elastomeric bitumen general adhesive
Installation	trowel or caulking gun
Packaging	5 gallon pail (18.9 L) & 310 ML tubes
Application	70 to 140 ft <sup>2</sup> /gal. (0.28 to 0.57 L/m <sup>2</sup> ), depending on surface

\* Data is represented by average values, unless noted otherwise.

## TESTING & APPROVALS

FLORIDA BUILDING CODE

MIAMI-DADE COUNTY  
APPROVED



**SOPREMA®**

[www.soprema.us](http://www.soprema.us)  
310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10158 - REV. 005220