

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

ALSAN RS Quartz Aggregate is mineral surfacing used to achieve an aesthetic finish, bond/wearing layer and/or non-skid wearing surface. ALSAN RS Quartz Aggregates are washed, kiln-dried, dust-free, angular grain quartz silica suitable for broadcasting available in natural and variety of other colors.

ALSAN RS Quartz Aggregates are available in 50 lb. (22.7kg) bags in two sizes:

- Grade 0: 0.4 – 0.8 mm
- Grade 1: 0.7 – 1.2 mm

Contact SOPREMA regarding specific colors and color matching capabilities.

### STORAGE

Always store closed containers in cool, ventilated and dry locations away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Approximate shelf life is twelve months from date of manufacture when properly stored sealed and unmixed.

### APPLICATION

ALSAN RS Quartz Aggregate is hand-broadcast into an appropriate coat of ALSAN RS resin, ALSAN RS Mortar or ALSAN RS 287 Color Finish Base. When applying a colored quartz finish, SOPREMA recommends blending a minimum of three different colored aggregates for the best aesthetic results. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods.

Refer to individual ALSAN RS product data sheets for additional information regarding mixing, Application and use.

