

SOPRAWAY

ADHESIVE

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

SOPRAWAY Adhesive is a solvent free, low odor, acrylic latex emulsion based adhesive designed for interior installation of SOPRAWAY NG2 rubber acoustic membranes.

STORAGE

Store the product in a well-ventilated area, away from heat and direct sunlight. Product can be stored for up to 12 months in the original sealed container.

APPLICATION

Surface must be clean and dry, free of oil, grease, dirt or debris. SOPRAWAY Adhesive is ready-to-use and no mixing is required. SOPRAWAY Adhesive is applied using a 1/8 in (3 mm) or 3/16 in (4.8 mm) V notched trowel. Application temperatures vary from 41°F (10°C) to 95°F (35°C). Curing time will be longer at lower temperatures.

APPLICATION



NOTCHED
TROWEL

QUICK FACTS

WEIGHT (lb/Gal)	WEIGHT (lb/container)	COVERAGE* 3/16 (4.5 mm) trowel (ft ²)	COVERAGE* 1/8 (3 mm) trowel (ft ²)	PACKAGING (Gal)
10 (1.19 kg/L)	50 (22.5 kg/container)	400 (37 m ²)	500 - 600 (46 - 55 m ²)	5 (18.59 L)

* Coverage rate is approximate and may vary due to the application technique and surface roughness.



SOPREMA[®]

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

TECHNICAL INFORMATION & TESTING

PROPERTIES	
Weight, lb/Gal (kg/L)	10.0 (1.19)
Weight, lb/container (kg/container)	50 (22.5)
Window of	Approximately 30 minutes
Flash point	Non-flammable
Freeze/thaw stability	Up to 14°F (-12°C)
Bonding to support, kg/cm	3.4
Physical state	Mastic
Base	Acrylic latex
Color	Beige
Packaging, Gal (L)	5.0 (18.9)