

# ANTIROCK® PRIMER

ANTIROCK® PRIMER  
PRODUCT #  
D36735 (5 gal)  
D36740 (53 gal)

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

ANTIROCK Primer is a blend of SBS modified bitumen, fast-evaporating solvents and adhesive enhancing additives. It is used to prime concrete and metal surfaces on civil engineering structures in order to improve the adhesion of heat-welded ANTIROCK waterproofing membranes.

### STORAGE

Store in a pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ANTIROCK Primer. Approximate shelf life is 12 months from date of manufacture when properly stored in sealed and unopened containers, in a cool and ventilated area.

### APPLICATION

Mix prior to application. ANTIROCK Primer can be applied to the approved area via brush, roller or spray equipment. ANTIROCK Primer is applied at a rate of 150-250 square feet per gallon over dry non porous substrates. Refer to the SOPREMA ANTIROCK specifications for additional application guidelines.

APPLICATION



BRUSH



ROLLER



SPRAY

QUICK FACTS

ASTM STANDARD	CONTAINER (gal)		COVERAGE RATE (ft <sup>2</sup> /gal)
D41	5 (18.9 L)	53 (200 L)	150-250 (3.7-6.1 m <sup>2</sup> /L)



**SOPREMA®**

[www.soprema.us](http://www.soprema.us)  
310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10373 - REV. 005619