




ROOFING & VATERPROOFING

SOPRA-TITE®CANTILEVER COPING

ROOFING



RELATED PRODUCTS

ELASTOPHENE FLAM

ELASTOPHENE Flam is composed of a proprietary formulation of elastomeric styrenebutadienestyrene (SBS) polymer modified bitumen and is reinforced with a high quality random glass fiber mat. The topside and underside are surfaced with polyolefin burn-off film to optimize heat welding.

SOPRA-TITE Cantilever Coping is designed for attachment to a parapet wall with a non-structural exterior building façade. Support brackets offer extra stability to the roof edge system when attachment is required up to 6 inches away from the outside façade. SOPRA-TITE Cantilever Coping has a full snap-on design with 16-gauge, galvanized steel anchor clips and factory-applied stainless steel springs to ensure long-term attachment. SOPRA-TITE Cantilever Coping is custom fabricated in sizes to meet specific job requirements and has pre-punched fastening holes to ensure proper attachment to the building substrate.

- Factory Mutual approved for wind uplift protection
- Compliant with the High Velocity Hurricane Zone of the Florida Building Code and ANSI/SPRI/FM 4435/ ES-1 Tested
- Corrosion resistant, stainless steel springs are factory attached to the anchor clips and provide long-term, positive spring loading
- Decreased labor costs due to ease of installation



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH