

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Mixture
Product name	: SBS Modified Bitumen Waterproofing Membrane
Synonyms	: ANTIROCK, COLPHENE 180 FR GR, COLPHENE 180 PS, COLPHENE 180 SANDED, COLPHENE 180 SP, COLPHENE 250 FR GR, COLPHENE FLAM 180, COLPHENE FLAM 180 FR GR, COLPHENE FLAM 250 FR GR, COLPHENE SANDED, COLPHENE SP 2.2, COLPHENE SP 3.0, COLPHENE STICK, COLPHENE STICK GR, COLVENT 180 TG, COLVENT FLAM 180 TG, COLVENT FLAM TG, COLVENT TG, ELASTOPHENE FLAM, ELASTOPHENE FLAM 2.2, ELASTOPHENE FLAM FR GR, ELASTOPHENE FLAM FR+ GR, ELASTOPHENE FLAM HR 3.0, ELASTOPHENE FLAM HS, ELASTOPHENE FLAM HS FR GR, ELASTOPHENE FLAM LS FR GR, ELASTOPHENE FLAM STICK, ELASTOPHENE FR GR, ELASTOPHENE FR+ GR, ELASTOPHENE HR FR GR, ELASTOPHENE HR SANDED 2.2, ELASTOPHENE HR SANDED 3.0, ELASTOPHENE HS FR GR, ELASTOPHENE HS SANDED, ELASTOPHENE LS FR GR, ELASTOPHENE PS 2.2, ELASTOPHENE PS 3.0, ELASTOPHENE SANDED 2.2, ELASTOPHENE SANDED 3.0, ELASTOPHENE SP 2.2, ELASTOPHENE SP 3.0, ELASTOPHENE STICK, ELASTOPHENE ULTRA-STICK, ELASTOPHENE ULTRA-STICK FR GR, LASTOBOND ECO, LASTOBOND SHIELD HT, Modified SOPRA G, SOPRA 4897, SOPRA IV, SOPRABASE S, SOPRABASE TG, SOPRAFIX BASE 611, SOPRAFIX BASE 612, SOPRAFIX BASE 613, SOPRAFIX BASE 614, SOPRAFIX BASE 622, SOPRAJOINT, SOPRALAST 50 TV ALU, SOPRALAST 50 TV ALU SANDED, SOPRALENE 180 FR GR, SOPRALENE 180 FR+ GR, SOPRALENE 180 PS 2.2, SOPRALENE 180 PS 3.0, SOPRALENE 180 SANDED, SOPRALENE 180 SANDED 2.2, SOPRALENE 180 SP 3.0, SOPRALENE 180 SP 3.0 CUT 13", SOPRALENE 180 SP 3.5, SOPRALENE 250 FR GR, SOPRALENE 250 FR+ GR, SOPRALENE 250 SANDED, SOPRALENE 250 SP 4.0, SOPRALENE FLAM 180, SOPRALENE FLAM 180 CUT 13", SOPRALENE FLAM 180 FR GR, SOPRALENE FLAM 180 FR+ GR, SOPRALENE FLAM 250, SOPRALENE FLAM 250 FR GR, SOPRALENE FLAM 250 FR+ GR, SOPRALENE FLAM STICK, SOPRALENE STICK, SOPRALENE STICK CUT 13", SOPRALENE ULTRA-STICK, SOPRALENE ULTRA-STICK FR GR, SOPRAVAP <sup>r</sup> , SOPRAVI, SOPRAWALK GR, ULTRA-STICK NAIL BASE, UNILAY

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Membranes used for all types of roofing needs, air barrier and waterproofing protection
------------------------------	---

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 1.3. Supplier

Manufacturer:  
SOPREMA INC.  
310 Quadral Dr.  
Wadsworth, OH 44281  
Tel: 1-800-356-3521

Distributors:  
SOPREMA Canada  
1675 Haggerty Street  
Drummondville (Quebec) J2C 5P7  
Tel: 1-819-478-8163

SOPREMA Canada  
44955 Yale Road West  
Chilliwack (BC) V2R 4H3  
CANADA  
Tel: 1-604-793-7100

SOPREMA USA  
12251 Seaway Road  
Gulfport (Mississippi) 39507  
UNITED STATES  
Tel: 1-228-701-1900

### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS US classification

Not classified

### 2.2. GHS Label elements, including precautionary statements

According to the corresponding national regulations there is no labelling obligation for this product.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Asphalt	CAS-No.: 8052-42-4	30 – 70	Carc. 1B, H350
Calcium carbonate	CAS-No.: 471-34-1	0 – 60	Not classified
distillates (petroleum), hydrotreated heavy naphthenic	CAS-No.: 64742-52-5	0 – 30	Carc. 1B, H350
Quartz	CAS-No.: 14808-60-7	7 – 13	Carc. 1A, H350
talc	CAS-No.: 14807-96-6	7 – 13	Not classified

A portion of crystalline silica can be present in the sand or granules spread on top of some membranes. The crystalline silica contained in the sand or granules is not likely to be found in ambient air in concentrations above the limits of exposure since the product adheres to the surface of the membrane.

Full text of hazard classes and H-statements : see section 16SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

No additional information available

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### SBS Modified Bitumen Waterproofing Membrane

No additional information available

#### Asphalt (8052-42-4)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Asphalt (Bitumen) fumes, as benzene-soluble aerosol
ACGIH OEL TWA	0.5 mg/m <sup>3</sup> (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: URT & eye irr. Notations: A4 (Not classifiable as a Human Carcinogen); BEIP
Regulatory reference	ACGIH 2021

#### distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

No additional information available

#### Calcium carbonate (471-34-1)

No additional information available

#### Quartz (14808-60-7)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 R
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2021

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Quartz (14808-60-7)

#### USA - OSHA - Occupational Exposure Limits

Local name	Silica, crystalline quartz, respirable dust
Remark (OSHA)	(3) See Table Z-3.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

### talc (14807-96-6)

#### USA - ACGIH - Occupational Exposure Limits

Local name	Talc (2009) Containing no asbestos fibers
ACGIH OEL TWA	2 mg/m <sup>3</sup>

#### USA - OSHA - Occupational Exposure Limits

Local name	Talc (containing no asbestos), respirable dust
Remark (OSHA)	(3) See Table Z-3.

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Various
Odour	: Asphalt
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Specific Gravity	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive limits	: Not applicable
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Asphalt (8052-42-4)

LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 Inhalation - Rat	> 0.0944 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Calcium carbonate (471-34-1)</b>	
LD50 oral rat	> 2000 mg/kg (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value)
LC50 Inhalation - Rat	> 3 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Experimental value)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Asphalt (8052-42-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>Quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

<b>Asphalt (8052-42-4)</b>	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.0207 mg/l air Animal: rat, Guideline: other:OECD 451
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

<b>Calcium carbonate (471-34-1)</b>	
LC50 - Fish [1]	> 100 % (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 100 % (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

<b>talc (14807-96-6)</b>	
LC50 - Fish [1]	> 100 g/l (24 h, Brachydanio rerio, Semi-static system)

### 12.2. Persistence and degradability

<b>Asphalt (8052-42-4)</b>	
Persistence and degradability	Not readily biodegradable in water. Not established.

<b>distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
Persistence and degradability	Not established.

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Calcium carbonate (471-34-1)</b>	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil. Not established.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>Quartz (14808-60-7)</b>	
Persistence and degradability	Biodegradability: not applicable. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

<b>talc (14807-96-6)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

<b>Asphalt (8052-42-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	> 6 (Calculated)
Bioaccumulative potential	Not bioaccumulative. Not established.

<b>distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
Bioaccumulative potential	Not established.

<b>Calcium carbonate (471-34-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-2.12 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

<b>Quartz (14808-60-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Bioaccumulative potential	No bioaccumulation data available. Not established.

### 12.4. Mobility in soil

<b>Calcium carbonate (471-34-1)</b>	
Ecology - soil	Adsorbs into the soil.

### 12.5. Other adverse effects

No additional information available



# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### 14.1. UN number

Not regulated for transport

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : Not applicable

#### 14.4. Packing group

Packing group (DOT) : Not applicable

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

##### DOT

No data available

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Asphalt	CAS-No. 8052-42-4	30 – 70%
---------	-------------------	----------

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

##### CANADA

#### Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)

# SBS Modified Bitumen Waterproofing Membrane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

### Asphalt (8052-42-4)

Listed on IARC (International Agency for Research on Cancer)

### Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Asphalt(8052-42-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Quartz(14808-60-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
talc(14807-96-6)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/25/2021

### Full text of H-statements

H350	May cause cancer.
------	-------------------

Safety Data Sheet (SDS), USA

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.