


# SOPRANATURE® EDGE RESTRAINT



APPLICATIONS

VEGETATED SOLUTIONS

PRODUCT DATA SHEET PD10201 - REV.029121

## DESCRIPTION:

SOPRANATURE Edge Restraints are a lightweight, rigid, aluminum, L-shaped restraints designed to retain planting media, stones, pavers and tiles in a vegetated roofing system. Multiple height options are available and can be ordered with a mill or black finish. Inside and outside corners are available for a complete assembly.

## STORAGE & HANDLING:

Store product in a clean, dry location to protect packaging until product is to be used.

## APPLICATION:


Place SOPRANATURE Edge Restraint on the protection or drainage layer, place aluminum sliding connector, and slide restraints together to lock into place. Refer to application guidelines.

## QUICK FACTS:

LENGTH (ft)	HEIGHT (in)	BASE WIDTH (in)	DEPTH (in)	THICKNESS (in)
8.0 (2.44 m)	4.5 (114.3 mm)	3.25 (82.6 mm)	4.0 (101.6 mm)	0.21 (5.33 mm)

Refer to back for additional sizes.

# SOPRANATURE<sup>®</sup> DRAIN BOX



APPLICATIONS

VEGETATED SOLUTIONS

## PRODUCT DATA SHEET

### PHYSICAL PROPERTIES:

PROPERTY	VALUE
Material	Aluminum
Colors	Mill Finish, Black
Thickness, in (mm)	0.21 (5.33)
Length, ft (m)	8 (2.44)
Flow Rate, gal/min/ft (l/min/m)	15 (56.78)
Tensile Strength (Ultimate) (min - max)	22.0 - 30.0
Tensile Strength (Yield) (min - max)	16.0 - 25.0
Elongation (Percent min in 2" or 4D)	8
Typical Brinell Hardness (500 kg load/10 mm ball)	60
Typical Ultimate Shearing Strength (ksi)	17
Typical Electrical Conductivity (%IACS)	55

### AVAILABLE SIZES - (More sizes available, please contact SOPREMA):

Height x Base Width (in)
3.00 x 3.25 (7.62 x 8.26 cm)
3.50 x 4.50 (8.89 x 11.43 cm)
4.50 x 3.25 (11.43 x 8.26 cm)
4.50 x 4.50 (11.43 x 11.43 cm)
5.50 x 6.50 (13.97 x 16.51 cm)
6.50 x 5.50 (16.51 x 13.97 cm)
7.50 x 8.50 (19.05 x 21.59 cm)
8.50 x 7.50 (21.59 x 19.05 cm)