

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : ALSAN TRAFIK RS 730 Flash
 Product code : ALSAN TRAFIK RS 730

1.2. Recommended use and restrictions on use

Industrial Use Only

1.3. Supplier

Manufacturer: SOPREMA, Inc.
 310 Quadral Dr.
 Wadsworth, OH 44281
 Tel: 1-800-356-3521

SOPREMA USA
 12251 Seaway Road
 Gulfport (Mississippi)
 39507 UNITED STATES
 Tel: 1-228-701-1900

Distributors:
 SOPREMA Canada
 44955 Yale Road West
 Chilliwack (BC) V2R 4H3 CANADA
 Tel: 1-604-793-7100

SOPREMA Canada
 1675 Haggerty Street
 Drummondville (Quebec) J2C 5P7
 Tel: 1-819-478-8163

1.4. Emergency telephone number

CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	Highly flammable liquid and vapor
Acute toxicity (oral) Category 4	Harmful if swallowed
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	May cause genetic defects
Carcinogenicity Category 1B	May cause cancer
Reproductive toxicity Category 1A	May damage fertility or the unborn child
Specific target organ toxicity (single exposure) Category 2	May cause damage to organs
Specific target organ toxicity (single exposure) Category 3	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 1	Causes damage to organs through prolonged or repeated exposure

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Highly flammable liquid and vapour
 Harmful if swallowed

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	<p>Causes skin irritation May cause an allergic skin reaction Causes serious eye irritation May cause respiratory irritation May cause genetic defects May cause cancer May damage fertility or the unborn child May cause damage to organs Causes damage to organs through prolonged or repeated exposure</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from ignition sources. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment Use explosion-proof electrical equipment Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe fumes or mist. Avoid breathing vapors. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace Wear personal protective equipment. If swallowed: Call doctor if you feel unwell If on skin: Wash with plenty of water If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower If inhaled: Remove person to fresh air and keep comfortable for breathing If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If exposed or concerned: Get medical advice/attention. Call doctor if you feel unwell Get medical advice/attention if you feel unwell. Specific treatment (see first aid measures on this label) Rinse mouth. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to meet all regulations</p>
-----------------------------------	--

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
31% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate	(CAS-No.) 80-62-6	12 - 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-Ethylhexyl acrylate	(CAS-No.) 103-11-7	14 - 14.5	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Toluene	(CAS-No.) 108-88-3	<= 10	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
N-butyl methacrylate	(CAS-No.) 97-88-1	<= 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
Lithium Chloride	(CAS-No.) 7447-41-8	0.5 - 1.1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Stoddard solvent	(CAS-No.) 8052-41-3	<= 1	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
Ethylbenzene	(CAS-No.) 100-41-4	<= 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Xylene	(CAS-No.) 1330-20-7	<= 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Naphthalene	(CAS-No.) 91-20-3	<= 1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
N-N-bis-(2-hydroxypropyl)-p-toluidine	(CAS-No.) 38668-48-3	0.5 - 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2, H319 STOT SE 2, H371
1-Methyl-2-pyrrolidone	(CAS-No.) 872-50-4	<= 0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 1A, H360 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see first aid measures on this label). If skin irritation or rash occurs: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/effects after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation.

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing fumes and vapors.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing vapors. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Use only outdoors or in a well-ventilated area. Do not breathe fumes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : children. Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)
Not applicable
2-Ethylhexyl acrylate (103-11-7)
Not applicable
Paraffin waxes and Hydrocarbon waxes (8002-74-2)
Not applicable
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)
Not applicable
Stoddard solvent (8052-41-3)
Not applicable
Ethylbenzene (100-41-4)
Not applicable
Naphthalene (91-20-3)
Not applicable
Toluene (108-88-3)
Not applicable
N-butyl methacrylate (97-88-1)
Not applicable
Aluminum hydroxide (Al(OH)3) (21645-51-2)
Not applicable
1-Methyl-2-pyrrolidone (872-50-4)
Not applicable
Xylene (1330-20-7)
Not applicable
Propylene glycol monomethyl ether acetate (108-65-6)
Not applicable
Silica, amorphous, fumed, crystalline-free (112945-52-5)
Not applicable
Formyl Morpholine (4394-85-8)
Not applicable
Lithium Chloride (7447-41-8)
Not applicable
N-N-bis-(2-hydroxypropyl)-p-toluidine (38668-48-3)
Not applicable
N-butyl acetate (123-86-4)
Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Wash hands and forearms thoroughly after handling.

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Materials for protective clothing:

Impervious clothing. Footwear (shoes, boots)

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Other information:

Do not eat, drink or smoke during use. Do not breathe spray. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Khaki Grey
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: $\approx 101\text{ }^{\circ}\text{C}$
Flash point	: $\approx 35\text{ }^{\circ}\text{C}$
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: $\approx 1.21\text{ g/cm}^3$
Relative density	: No data available
Solubility	: insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: 2,500 centipoises (Visco Brookfield LVT)
Viscosity, kinematic	: No data available
Viscosity, dynamic	: $\approx 10,000\text{ cP}$
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous fumes. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

ALSAN TRAFIK RS 730 Flash	
ATE US (oral)	446.3896586476 mg/kg body weight
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3600 mg/kg
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)	
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 10 mg/l (Exposure time: 1 h)
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15400 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.4 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat (mg/l)	> 340 mg/m ³ (Exposure time: 1 h)
ATE US (oral)	1110 mg/kg body weight
ATE US (dermal)	1120 mg/kg body weight
Toluene (108-88-3)	
LD50 oral rat	≈ 636 mg/kg
LD50 dermal rabbit	≈ 1410 mg/kg
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	4900 mg/l/4h
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
LD50 oral rat	> 5000 mg/kg
1-Methyl-2-pyrrolidone (872-50-4)	
LD50 oral rat	3914 mg/kg
LD50 dermal rabbit	8 g/kg
LC50 inhalation rat (mg/l)	> 5.1 mg/l/4h
ATE US (oral)	3914 mg/kg body weight
ATE US (dermal)	8000 mg/kg body weight
Xylene (1330-20-7)	
ATE US (dermal)	1100 mg/kg body weight

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene (1330-20-7)	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 oral rat	8532 mg/kg
LD50 dermal rabbit	> 5 g/kg
ATE US (oral)	8532 mg/kg body weight

Silica, amorphous, fumed, crystalline-free (112945-52-5)	
LD50 oral rat	3160 mg/kg
ATE US (oral)	3160 mg/kg body weight

Lithium Chloride (7447-41-8)	
ATE US (oral)	500 mg/kg body weight

N-N-bis-(2-hydroxypropyl)-p-toluidine (38668-48-3)	
ATE US (oral)	5 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Silica, amorphous, fumed, crystalline-free (112945-52-5)	
IARC group	3 - Not classifiable

Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity – single exposure	: May cause damage to organs. May cause respiratory irritation.

Specific target organ toxicity – repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
--	---

Aspiration hazard	: Not classified
-------------------	------------------

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
---	---

Symptoms/effects after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation.
-----------------------------------	--

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ethylbenzene (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
Naphthalene (91-20-3)	
LC50 fish 1	5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
Toluene (108-88-3)	
LC50 fish 1	13 mg/l
EC50 Daphnia 1	313 mg/l
ErC50 (algae)	245 mg/l
ErC50 (other aquatic plants)	12.5 mg/l
1-Methyl-2-pyrrolidone (872-50-4)	
LC50 fish 1	832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Propylene glycol monomethyl ether acetate (108-65-6)	
LC50 fish 1	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

ALSAN TRAFIK RS 730 Flash	
Persistence and degradability	Not established.
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)	
Persistence and degradability	Not established.
Stoddard solvent (8052-41-3)	
Persistence and degradability	Not established.
Toluene (108-88-3)	
Persistence and degradability	Not established.
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

ALSAN TRAFIK RS 730 Flash	
Bioaccumulative potential	Not established.
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)	
Bioaccumulative potential	Not established.
Stoddard solvent (8052-41-3)	
Bioaccumulative potential	Not established.

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
BCF fish 1	15
Log Pow	3.2
Naphthalene (91-20-3)	
BCF fish 1	30 - 430
Log Pow	3.6
Toluene (108-88-3)	
Bioaccumulative potential	Not established.
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Bioaccumulative potential	Not established.
1-Methyl-2-pyrrolidone (872-50-4)	
Log Pow	-0.46 (at 25 °C)
Propylene glycol monomethyl ether acetate (108-65-6)	
Log Pow	0.43

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

Ethylbenzene (100-41-4)	
1990 Hazardous Air Pollutant (Clean Air Act)	Yes

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to meet all regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

DOT Proper Shipping Name : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons)
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length ; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No.(IATA) : 1263
Proper Shipping Name (IATA) : PAINT
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate	CAS-No. 80-62-6	12 - 40%
2-Ethylhexyl acrylate	CAS-No. 103-11-7	14 - 14.5%
N-butyl methacrylate	CAS-No. 97-88-1	<= 10%
Xylene	CAS-No. 1330-20-7	<= 1%
Silica, amorphous, fumed, crystalline-free	CAS-No. 112945-52-5	1 - 2%
Formyl Morpholine	CAS-No. 4394-85-8	0.5 - 1.1%
Lithium Chloride	CAS-No. 7447-41-8	0.5 - 1.1%
N-N-bis-(2-hydroxypropyl)-p-toluidine	CAS-No. 38668-48-3	0.5 - 1%
N-butyl acetate	CAS-No. 123-86-4	<= 1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Ethylbenzene	CAS-No. 100-41-4	<= 1%
Naphthalene	CAS-No. 91-20-3	<= 1%
Toluene	CAS-No. 108-88-3	<= 10%

Ethylbenzene (100-41-4)

CERCLA RQ 1000 lb

Naphthalene (91-20-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

Toluene (108-88-3)

CERCLA RQ 1000 lb

1-Methyl-2-pyrrolidone (872-50-4)

EPA TSCA Regulatory Flag R - R - indicates a substance that is the subject of a TSCA section 6 risk management rule.

Propylene glycol monomethyl ether acetate (108-65-6)

EPA TSCA Regulatory Flag P - P - indicates a commenced Premanufacture Notice (PMN) substance.

15.2. International regulations

CANADA

No additional information available

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the Canadian DSL (Domestic Substances List)

Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)

Listed on the Canadian DSL (Domestic Substances List)

Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

Naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Toxic Substance (CEPA – Schedule I) Yes

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aluminum hydroxide (Al(OH)₃) (21645-51-2)

Listed on the Canadian DSL (Domestic Substances List)

1-Methyl-2-pyrrolidone (872-50-4)

Listed on the Canadian DSL (Domestic Substances List)

Propylene glycol monomethyl ether acetate (108-65-6)

Listed on the Canadian DSL (Domestic Substances List)

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Stoddard solvent (8052-41-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethylbenzene (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Naphthalene (91-20-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Aluminum hydroxide (Al(OH)₃) (21645-51-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1-Methyl-2-pyrrolidone (872-50-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Propylene glycol monomethyl ether acetate (108-65-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) (136-52-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stoddard solvent (8052-41-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Naphthalene (91-20-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Aluminum hydroxide (Al(OH)3) (21645-51-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

1-Methyl-2-pyrrolidone (872-50-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Propylene glycol monomethyl ether acetate (108-65-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	54 µg/day	

Naphthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	5.8 µg/day	

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	Yes	Yes	7000	

1-Methyl-2-pyrrolidone (872-50-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		3200 µg/day inhalation

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Stoddard solvent (8052-41-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Ethylbenzene (100-41-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

ALSAN TRAFIK RS 730 Flash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Naphthalene (91-20-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Toluene (108-88-3)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

1-Methyl-2-pyrrolidone (872-50-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H300	Fatal if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H371	May cause damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.