



ALSAN TRAFIK PU 420 OR PU 421
 POLYURETHANE TOP COAT APPLIED
 OVER ACCEPTABLE AGGREGATE

ALSAN TRAFIK PU 420 OR PU 421
 POLYURETHANE TOP COAT
 SANDED TO REFUSAL &
 CURED 2 - 4 HOURS

ALSAN TRAFIK PU 220
 POLYURETHANE BASE COAT
 CURED 2 - 4 HOURS

ALSAN TRAFIK EP 140 OR
 EP 141 EPOXY PRIMER

ACCEPTABLE SUBSTRATE
 PREPARED PER SOPREMA
 REQUIREMENTS

SOPREMA DETAIL DRAWINGS: REFER TO SOPREMA AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY SOPREMA FOR THE SOLE PURPOSE OF ISSUING A SOPREMA WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.



SOPREMA®

US CORPORATE ADDRESS
 310 QUADRAL DRIVE
 WADSWORTH, OHIO 44281
www.soprema.us
 Tel:330.334.0066

PROJECT:

TITLE:
**ALSAN TRAFIK PU DECK COATING
 VEHICULAR TRAFFIC (DRIVE LANES)
 ASSEMBLY**

DRAWN BY: SOPREMA TECHNICAL SUPPORT, DWALDRON		
NO.:	REVISION:	DATE:
DATE: 8-5-2020	DRAWING NUMBER: US.PDC.01.V3A	
SCALE: NTS	PDC_01_V3A	

USAGE OF THIS DETAIL IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAILS. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.