



ALSAN RS PRIMER OR APPROVED MOISTURE MITIGATION PRIMER APPLIED TO PREPARED SUBSTRATE (TYP.)

ACCEPTABLE ALSAN RS TRAFFIC SURFACING - SEE SPECIFICATION FOR OPTIONS. DO NOT EXTEND ALSAN RS SURFACING ONTO COVER/GRATE.

ALSAN RS MORTAR APPLIED CONTINUOUSLY OVER ALSAN TRAFIK RS MEMBRANE.

ALSAN TRAFIK RS FIELD MEMBRANE OVERLAPPED 4" (100 mm) MINIMUM ONTO DRAIN FLASHING.

(1) PLY ALSAN TRAFIK RS FLASH MEMBRANE TARGET EXTEND OVER FINGER FLASHING & ONTO DRAIN BOWL FLANGE.

DRAIN COVER/GRATE SET IN BED OF ALSAN RS MORTAR TO CREATE SMOOTH TRANSITION TO TRAFFIC SURFACE (TYP.)

4" (100 mm)
MINIMUM

RECESS CONCRETE AS REQUIRED TO INSTALL DECK DRAIN ASSEMBLY.

PREPARE, LEVEL & PATCH SUBSTRATE W/ALSAN RS MORTAR AFTER PRIMING & PRIOR TO APPLICATION OF ALSAN TRAFIK RS WATERPROOFING MEMBRANE (TYP.)

ALSAN TRAFIK RS FLASH MEMBRANE FLASHING W/ 3" (75 mm) FINGERS EXTENDED 2" (50 mm) INTO PREPARED & PRIMED DRAIN BOWL.

ACCEPTABLE DRAIN ASSEMBLY-ADJUST COLLAR AS REQUIRED TO ASSURE TOP OF GRATE IS FLUSH W/TRAFFIC SURFACE. PREPARE DRAIN BOWL AS REQUIRED FOR ALSAN TRAFIK RS MEMBRANE APPLICATION.

SOPREMA DETAIL DRAWINGS: REFER TO SOPREMA AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY SOPREMA FOR THE SOLE PURPOSE OF ISSUING A SOPREMA WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.



US CORPORATE ADDRESS
310 QUADRAL DRIVE
WADSWORTH, OHIO 44281
www.soprema.us
Tel: 330.334.0066

PROJECT:

TITLE:

**ALSAN TRAFIK RS FULLY REINFORCED
WATERPROOFING & SURFACING
TRAFFIC DECK DRAIN FLASHING**

DRAWN BY: SOPREMA TECHNICAL SUPPORT, DWALDRON

NO.:

REVISION:

DATE:

DATE: 1-15-2022

SCALE: NTS

DRAWING NUMBER:

US.RTR.07.D01

USAGE OF THIS DETAIL IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAILS. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.