ALSAN® RS QUARTZ AGGREGATE



Always store in a sealed bag or container in a cool, dry

ALSAN RS Quartz Aggregate is hand-broadcast into an

appropriate coat of ALSAN RS resin, ALSAN RS Mortar or

ALSAN RS 287 Color Finish Base. When applying a colored

quartz finish, SOPREMA recommends blending a minimum of three different colored aggregates for the best aesthetic

results. The applicator is responsible for ensuring conditions

are appropriate to proceed with proper application methods.

additional information regarding mixing, Application and use.

ROSURIENT

Refer to individual ALSAN RS product data sheets for

and ventilated location. Do not store in temperatures

below 32°F (0°C) or above 77°F (25°C).

STORAGE:

APPLICATION:



PRODUCT DATA SHEET PDS10362 - REV.220423

ROOFING

DESCRIPTION:

Mineral Surfacing

ALSAN RS Quartz Aggregate is mineral surfacing used to achieve an aesthetic finish, bond/wearing layer and/or non-skid wearing surface. ALSAN RS Quartz Aggregates are washed, kiln-dried, dust-free, angular grain quartz silica suitable for broadcasting available in natural and variety of other colors.

ALSAN RS Quartz Aggregates are available in 50 lb. (22.7kg) bags in two grades:

- Grade 0: 0.4-0.8 mm (40-S: 40 mesh spherical)
- Grade 1: 0.7-1.2 mm (25-A: 25 mesh angular)

Natural Quartz is also available in 0, 1 & 2 sizes.

SANDAL WOOD

CALICO - 2

AVAILABLE COLORS:

ICE	ICE TROWEL	BLUE WATER	GRANITE	SEAMIST - 2	OCEAN - 2	ALFALFA	EMERALD
OXEN	NIGHTLIFE	BLACK GRANITE	BLUE GRANITE	STONE BLUE	SAHARA	BISQUE	SAND

ROCOCO - 2

REACH



DAYBREAK

CARAMEL

COLONIAL BRICK

ALSAN® RS QUARTZ AGGREGATE





PRODUCT DATA SHEET PDS10362 - REV.22042

ROOFING

AVAILABLE SOLID COLORS:

Mineral Surfacing



