

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SBL Roof Cement

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesive used for roofing, waterproofing and flashing

1.3. Supplier

Manufacturer:
SOPREMA INC.
310 Quadral Dr.
Wadsworth, OH 44281
Tel: 1-800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) V2R 4H3
CANADA
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport (Mississippi) 39507
UNITED STATES
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | | |
|---|------|---|
| Flammable liquids, Category 3 | H226 | Flammable liquid and vapour. |
| Skin corrosion/irritation, Category 2 | H315 | Causes skin irritation. |
| Serious eye damage/eye irritation, Category 2 | H319 | Causes serious eye irritation. |
| Germ cell mutagenicity, Category 1B | H340 | May cause genetic defects. |
| Carcinogenicity, Category 1B | H350 | May cause cancer. |
| Specific target organ toxicity — Repeated exposure, Category 1 | H372 | Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation). |
| Hazardous to the aquatic environment — Acute Hazard, Category 2 | H401 | Toxic to aquatic life |
| Hazardous to the aquatic environment — Chronic Hazard, Category 3 | H412 | Harmful to aquatic life with long lasting effects. |

Full text of H-statements: see section 16

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H340 - May cause genetic defects.
H350 - May cause cancer.
H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapours.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P280 - Wear nitrile gloves
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use ABC-powder, BC-powder, dry sand, foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of container in accordance with local, regional or national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|--------------------------------|-----------------------|-----------|---|
| Asphalt | CAS-No.: 8052-42-4 | 40 – 70 | Carc. 1B, H350 |
| Stoddard solvent | CAS-No.: 8052-41-3 | 10 – 25 | Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304 |
| attapulgit | CAS-No.: 12174-11-7 | 1 – 20 | Carc. 2, H351 |
| Trade Secret #34-1672818-1025* | CAS-No.: Trade Secret | 0.1 - 2.5 | Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|---|---|
| Potential adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/effects | : Causes damage to organs through prolonged or repeated exposure. |
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after eye contact | : Eye irritation. |
| Symptoms/effects after ingestion | : May be fatal if swallowed and enters airways. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.
Explosion hazard : May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|--|
| Additional hazards when processed | : Handle empty containers with care because residual vapours are flammable. |
| Precautions for safe handling | : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------|---|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment. Ground/bond container and receiving equipment. |
| Storage conditions | : Keep only in the original container in a cool, well ventilated place away from : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. Heat sources. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SBL Roof Cement

No additional information available

Asphalt (8052-42-4)

USA - ACGIH - Occupational Exposure Limits

| | |
|----------------------|---|
| Local name | Asphalt (Bitumen) fumes, as benzene-soluble aerosol |
| ACGIH OEL TWA | 0.5 mg/m ³ (Inhalable fraction) |
| Remark (ACGIH) | TLV® Basis: URT & eye irr. Notations: A4 (Not classifiable as a Human Carcinogen); BEIP |
| Regulatory reference | ACGIH 2021 |

attapulgite (12174-11-7)

No additional information available

Stoddard solvent (8052-41-3)

USA - ACGIH - Occupational Exposure Limits

| | |
|---------------------|------------------|
| Local name | Stoddard solvent |
| ACGIH OEL TWA [ppm] | 100 ppm |

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stoddard solvent (8052-41-3)

Remark (ACGIH) : Eye, skin, & kidney dam;

Regulatory reference : ACGIH 2021

USA - OSHA - Occupational Exposure Limits

Local name : Stoddard solvent

OSHA PEL TWA [1] : 2900 mg/m³

OSHA PEL TWA [2] : 500 ppm

Regulatory reference (US-OSHA) : OSHA Annotated Table Z-1

Trade Secret #34-1672818-1025

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear nitrile gloves protective gloves

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Black
Odour : characteristic
Odour threshold : No data available
pH : No data available
Melting point : Not applicable

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|--------------------------------|
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : Flammable liquid and vapour. |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Specific Gravity | : No data available |
| Density | : ≈ 1.05 g/cm ³ |
| Solubility | : Insoluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

VOC content : ≈ 206 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Sparks. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

Asphalt (8052-42-4)

| | |
|---------------|--------------------|
| LD50 oral rat | > 2000 mg/kg (Rat) |
|---------------|--------------------|

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Asphalt (8052-42-4)

| | |
|-----------------------|--|
| LD50 dermal rabbit | > 2000 mg/kg (Rabbit) |
| LC50 Inhalation - Rat | > 0.0944 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |

Stoddard solvent (8052-41-3)

| | |
|-----------------------------------|----------------------------------|
| LD50 oral rat | 5000 mg/kg Source: ChemIDplus |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : May cause genetic defects. |
| Carcinogenicity | : May cause cancer. |

Asphalt (8052-42-4)

| | |
|------------|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
|------------|--------------------------------------|

attapulгите (12174-11-7)

| | |
|------------------------|---|
| IARC group | 2B - Possibly carcinogenic to humans, 3 - Not classifiable |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation). |

Asphalt (8052-42-4)

| | |
|---|--|
| LOAEC (inhalation, rat,dust/mist/fume, 90 days) | 0.0207 mg/l air Animal: rat, Guideline: other:OECD 451 |
|---|--|

Stoddard solvent (8052-41-3)

| | |
|---|---|
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : No data available |
| Potential adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/effects | : Causes damage to organs through prolonged or repeated exposure. |
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after eye contact | : Eye irritation. |
| Symptoms/effects after ingestion | : May be fatal if swallowed and enters airways. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

SBL Roof Cement

| | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

Asphalt (8052-42-4)

| | |
|-------------------------------|--|
| Persistence and degradability | Not readily biodegradable in water. Not established. |
|-------------------------------|--|

attapulгите (12174-11-7)

| | |
|-------------------------------|--|
| Persistence and degradability | Biodegradability: not applicable. No (test)data on mobility of the substance available. Not established. |
|-------------------------------|--|

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| attapulgate (12174-11-7) | |
|---------------------------------|------------------|
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |
| Stoddard solvent (8052-41-3) | |
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| SBL Roof Cement | |
|---|---|
| Bioaccumulative potential | Not established. |
| Asphalt (8052-42-4) | |
| Partition coefficient n-octanol/water (Log Pow) | > 6 (Calculated) |
| Bioaccumulative potential | Not bioaccumulative. Not established. |
| attapulgate (12174-11-7) | |
| Bioaccumulative potential | No bioaccumulation data available. Not established. |
| Stoddard solvent (8052-41-3) | |
| Partition coefficient n-octanol/water (Log Pow) | 3.16 – 7.06 Source: ICSC |
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

| attapulgate (12174-11-7) | |
|--------------------------|---|
| Ecology - soil | No (test)data on mobility of the substance available. |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of container in accordance with local, regional or national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container.
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1993

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



14.4. Packing group

Packing group (DOT) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

| | | |
|-------------------------------|--------------------|------------|
| Asphalt | CAS-No. 8052-42-4 | 40 – 70% |
| attapulgite | CAS-No. 12174-11-7 | 1 – 20% |
| Stoddard solvent | CAS-No. 8052-41-3 | 10 – 25% |
| Trade Secret #34-1672818-1025 | CAS-No. | 0.1 - 2.5% |

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)

attapulgite (12174-11-7)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

Trade Secret #34-1672818-1025

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Asphalt (8052-42-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

WARNING:

This product can expose you to attapulgite, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Component | State or local regulations |
|-----------------------------|---|
| Asphalt(8052-42-4) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Stoddard solvent(8052-41-3) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |

SBL Roof Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/28/2021
Other information : None.

| Full text of H-statements | |
|---------------------------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H401 | Toxic to aquatic life |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Safety Data Sheet (SDS), USA

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.