

# SAFETY DATA SHEET



## SECTION 1 IDENTIFICATION

|                         |   |
|-------------------------|---|
| <b>Product Name</b>     | Bitutak MB, Bitutak MB Mineral. Bitutak MB Mineral-CR<br>Bitutak Cold, Bitutak Cold Mineral |
| <b>Recommended Use</b>  | Waterproofing membrane for low-sloped roofs   |
| <b>Restrictions</b>     | Contact Manufacturer  |
| <b>Manufacturer</b>     | SOPREMA, Inc.   |
| <b>Address</b>          | 4821 Chelsea Avenue<br>Kansas City, MO 64130  |
| <b>Phone Number</b>     | (800) 334-0066  |
| <b>Emergency Number</b> | (800) 424-9300 (CHEMTREC)   |

## SECTION 2 HAZARDS

|                                 |  |
|---------------------------------|--|
| <b>GHS Classification</b>       | As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, Performance Roof Systems would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. |
| <b>Hazard Pictographs</b>       | Not Applicable   |
| <b>Signal Word</b>              | Not Applicable   |
| <b>Hazard Statements</b>        | Not Applicable   |
| <b>Precautionary Statements</b> | P201 - Obtain special instructions before use<br>P202 - Do not handle until all safety precautions have been read and understood<br>P260 - Do not breathe fume, gas, vapors<br>P264 - Wash hands, forearms and face thoroughly after handling<br>P270 - Do not eat, drink or smoke when using this product<br>P280 - Wear protective gloves and clothing   |
| <b>Response</b>                 | P301+P310 - If swallowed: Immediately call a Poison Center or doctor/physician.<br>Do not induce vomiting.<br>P303+P361+P353 - If on skin (or hair), Take off immediately all contaminated clothing. Rinse skin with water/shower<br>P303+P340 - If inhaled, remove person to fresh air and keep comfortable for breathing<br>P305+P351+P338 - If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing<br>P308+P313 - If exposed or concerned, get medical advice/attention<br>P314 - Get medical advice/attention if you feel unwell<br>P370+P378 - In case of fire: Use carbon dioxide (CO <sub>2</sub> ), foam, dry extinguishing powder to extinguish  |
| <b>Storage</b>                  | P403+P235 - Store in well-ventilated place. Keep cool  |
| <b>Disposal</b>                 | P501 - Dispose of contents and/or container in accordance with local, regional and national regulations  |

### SECTION 3 COMPOSITION

#### Chemical Composition

| COMPONENT                       | CAS NUMBER | PERCENT BY WEIGHT | GHS CLASSIFICATION |
|---------------------------------|------------|-------------------|--------------------|
| Asphalt <sup>1</sup>            | 8052-42-4  | 20 - 60           | Carc. 1B, H350     |
| Limestone <sup>1</sup>          | 1317-65-3  | 10 - 35           | Not classified     |
| Silica Crystalline <sup>2</sup> | 14808-60-7 | 1 - 12            | Carc. 1A, H350     |

**Note:** The above components and their percentages are provided for health and safety purposes, ONLY. This document should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

<sup>1</sup> Component is not likely to occur above the limits of exposure considering its incorporated into the mixture and/or provided use.

<sup>2</sup> Concentrations above the limit of exposure are not likely to be found in the ambient air due to adhesion to the membrane's surface.

### SECTION 4 FIRST AID MEASURES

|                                      |  |
|--------------------------------------|--|
| <b>Eyes</b>                          | If foreign matter enters eyes, immediately flush with large amounts of potable water for at least 15 minutes or until irritation subsides. Get medical attention if irritation persists. |
| <b>Skin</b>                          | Remove contaminated clothing and wash with soap and water.   |
| <b>Inhalation</b>                    | Remove affected person from source of exposure.  |
| <b>First-Aid, Ingestion</b>          | Consult a physician if unusual reaction is noted. Product is not intended nor is it likely to be ingested or eaten.  |
| <b>Symptoms, Acute &amp; Delayed</b> | <b>Refer to Section 11 - Toxicological Information</b>   |
| <b>Immediate Medical Attention</b>   | All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials.               |

### SECTION 5 FIRE FIGHTING MEASURES

|  |   |
|--|---|
| <b>Flash Point</b>                       | > 520-650°F (ASTM D92)  |
| <b>Hazardous Products of Combustions</b> | Carbon dioxide, carbon monoxide and partially burned carbon   |
| <b>Extinguishing Media</b>               | Water spray, foam, CO2 or dry chemical extinguishers  |
| <b>Firefighting instruction</b>          | Burning of this product will produce thick black smoke  |
| <b>Explosion Hazard</b>                  | None  |
| <b>Protection Gear</b>                   | Firefighters should wear full face, self contained breathing apparatus and impervious protective clothing to avoid smoke inhalation and lack of oxygen. |

### SECTION 6 ACCIDENTAL RELEASE MEASURES

|  |  |
|--|--|
| <b>Personal Precautions</b>                                | No special precautions should be necessary if material is used under ordinary conditions and as recommended.   |
| <b>Personal Precautions</b>                                | No emergency procedures should be necessary if material is used under ordinary conditions as recommended.  |
| <b>Environmental Precautions</b>                           | Avoid release into the environment.  |
| <b>Method and Materials for Containment &amp; Clean Up</b> | Pick up large pieces. Vacuum dust. If sweeping is necessary, use a dust suppressant such as water. These procedures will help to minimize potential exposures. Scoop up material and put into a suitable container for disposal as a nonhazardous waste. |

ABBREVIATION KEY

ASTM = American Society for Testing and Materials (International)

### SECTION 7 COMPOSITION

|                 |  |
|-----------------|--|
| <b>Handling</b> | Use this product with adequate ventilation. Avoid breathing dusts or fumes generated from cutting or heating this material. Always wash work clothes separately from other clothing. Wash thoroughly after handling. <b>Use personal protective equipment as described in Section 8.</b> |
| <b>Storage</b>  | Keep containers cool, dry and away from sources of ignition. <b>DO NOT STORE NEAR HEAT, SPARKS, FLAME, OTHER SOURCES OF IGNITION OR STRONG OXIDIZERS.</b>  |

### SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

|  |  |
|--|--|
| <b>Engineering Measures/Controls</b>   | Adequate ventilation systems as needed to control concentrations of airborne contaminants. |
| <b>General Industrial Hygiene</b>      | Use good industrial hygiene practices in handling this material.                           |
| <b>Environmental Exposure Controls</b> | Follow best practice for site management and disposal of waste.                            |

### PERSONAL PROTECTIVE EQUIPMENT

#### Pictographs



|                   |   |
|-------------------|---|
| <b>Eyes/Face</b>  | Safety glasses with side shields<br>Follow the national guidelines concerning the use of protective eye wear. |
| <b>Hand</b>       | Protective Gloves<br>Leather or cotton gloves may be worn to prevent skin contact and irritation.             |
| <b>Skin/Body</b>  | Normal work clothing (long sleeved shirts, long pants and smooth bottom work shoes) is recommended.           |
| <b>Inhalation</b> | Use NIOSH or MSHA approved respiratory protective equipment when ventilation is insufficient.                 |

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

|   |                     |
|---|---------------------|
| <b>Physical State</b>                       | Solid               |
| <b>Appearance</b>                           | black membrane      |
| <b>Odor</b>                                 | Slight asphalt odor |
| <b>Odor Threshold</b>                       | No data available   |
| <b>pH</b>                                   | No data available   |
| <b>Relative Evaporation Rate</b>            | No data available   |
| <b>Boiling Point</b>                        | > 900 °F; > 482°C   |
| <b>Freezing Point</b>                       | No data available   |
| <b>Flash Point</b>                          | 520 - 650 °F        |
| <b>Auto-ignition Temperature</b>            | No data available   |
| <b>Decomposition Temperature</b>            | No data available   |
| <b>Specific Gravity (H<sub>2</sub>O =1)</b> | No data available   |
| <b>Vapor pressure</b>                       | No data available   |
| <b>Vapor Density (AIR=1)</b>                | No data available   |
| <b>Solubility in Water</b>                  | NIL                 |

ABBREVIATION KEY

# SAFETY DATA SHEET



## SECTION 10 STABILITY AND REACTIVITY

|                                 |   |
|---------------------------------|---|
| <b>Stability</b>                | Stable at room temperature under normal storage and handling conditions.                            |
| <b>Reactivity</b>               | Upon combustion CO and CO <sub>2</sub> are formed   |
| <b>Conditions to Avoid</b>      | Strong oxidizers, no spark or open flame and high temperatures                                      |
| <b>Hazardous Decomposition</b>  | Under normal conditions of storage and use, hazardous decomposition products should not be produced |
| <b>Hazardous Polymerization</b> | Will not occur  |

## SECTION 11 TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

|                          |   |
|--------------------------|---|
| <b>Eyes</b>              |   |
| <b>Acute (Immediate)</b> | Mechanical irritation may occur in contact with particles.  |
| <b>Chronic (Delayed)</b> | No data available   |
| <b>Skin</b>              |   |
| <b>Acute (Immediate)</b> | Mechanical abrasion may occur in contact with skin. Thermal burns when handled at elevated temperatures.  |
| <b>Chronic (Delayed)</b> | No data available   |
| <b>Inhalation</b>        |   |
| <b>Acute (Immediate)</b> | For torch-on applications, inhalation of fumes may result in irritation, especially if the product is over heated above recommended temperatures.   |
| <b>Chronic (Delayed)</b> | This product contains crystalline silica which is listed by IARC as a suspect carcinogen. Silicosis (pulmonary fibrosis or severe lung scarring) may occur if exposed to high levels or repeated encounters with dust. Exposure to airborne particles that exceed the limits listed may cause lung cancer. This product also contains petroleum asphalt. If heated, there is limited evidence that derivatives of asphalt fumes may cause carcinogenic effects in animals. There is inadequate evidence to support that asphalt fumes alone are carcinogenic to humans. |
| <b>Ingestion</b>         |   |
| <b>Acute (Immediate)</b> | Product is not intended nor is it likely to be ingested or eaten.   |
| <b>Chronic (Delayed)</b> | No data available   |

### Component Analysis

| COMPONENT          | CAS NUMBER | ORAL LD50<br>(mg/kg) | DERMAL LD50<br>(mg/kg) | INHALATION LC50<br>(mg/L) |
|--------------------|------------|----------------------|------------------------|---------------------------|
| Asphalt            | 8052-42-4  | >2,000 (rat)         | >2,000 (rabbit)        | <0.094 (rat)              |
| Limestone          | 1317-65-3  | 500 (rat)            | N/A                    | >1 (rat)                  |
| Silica Crystalline | 14808-60-7 | >2,000 (rat)         | >2,000 (rat)           | >3 (rat)                  |

|                                  |   |
|----------------------------------|---|
| <b>Component Carcinogenicity</b> | Asphalt (8052-52-4)<br>IARC: Group 2B - Possibly carcinogenic to humans<br>Crystalline silica (14808-60-7)<br>IARC: Group 1 - Known Human Carcinogen (IARC Monograph 68 [1997]) |
| <b>Mutagenicity</b>              | Based on available data, the classification criteria are not met.   |
| <b>STOT Single Exposure</b>      | Based on available data, the classification criteria are not met.   |
| <b>STOT Repeated Exposure</b>    | May causes damage to (lungs) through prolonged or repeated exposure (inhalation).   |

ABBREVIATION KEY

IARC = International Agency for Research on Cancer  
LC50 = Lethal concentration, 50 Percent

LD50 = Lethal dose, 50 percent  
STOT = Specific Target Organ Toxicity

# SAFETY DATA SHEET



## SECTION 12 ECOLOGICAL INFORMATION

|                                 |  |
|---------------------------------|--|
| <b>General</b>                  | Employ best management practices to prevent this material from entering storm sewer systems, waterways or otherwise impacting plant and animal species.                    |
| <b>Component Analysis</b>       | No Data  |
| <b>Environmental Transport</b>  | No Data  |
| <b>Environment Degradation</b>  | No Data  |
| <b>Soil Absorption/Mobility</b> | No Data  |
| <b>Other Information</b>        | This product has not been tested. Based on information related to all raw materials in the finished product it is not expected to harm ecosystems through its applied use. |

## SECTION 13 DISPOSAL CONSIDERATIONS

|                        |  |
|------------------------|--|
| <b>Product Waste</b>   | The transportation, storage, treatment and dispose of this waste must be conducted in accordance with all applicable federal, state and local regulations. |
| <b>Packaging Waste</b> | The transportation, storage, treatment and dispose of this waste must be conducted in accordance with all applicable federal, state and local regulations. |

## SECTION 14 TRANSPORT INFORMATION

|                                   |  |
|-----------------------------------|--|
| <b>Transportation Regulations</b> | This product is not regulated as a hazardous material in transportation. |
|-----------------------------------|--|

## SECTION 15 TRANSPORT INFORMATION

|                                |   |
|--------------------------------|---|
| <b>TSCA Inventory</b>          | Components are listed   |
| <b>DSL Inventory</b>           | Components are listed   |
| <b>WHMIS Classification</b>    | Controlled Product Classification: D2A, based on the IARC classification of crystalline silica and limestone  |
| <b>Sara 313</b>                | None present  |
| <b>Sara 311/312 Categories</b> | None present  |
| <b>CERCLA</b>                  | None present  |
| <b>CA Proposition 65</b>       | This product can expose you to chemicals including Silica, crystalline (#14808-60-7) which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> . |

### Right to Know States

| COMPONENT          | CAS NUMBER | STATES                 |
|--------------------|------------|------------------------|
| Asphalt            | 8052-42-4  | CA, MA, NJ, PA RI      |
| Limestone          | 1317-65-3  | MA, MN, PA             |
| Silica Crystalline | 14808-60-7 | CA, MA, MN, NJ, PA, RI |

ABBREVIATION KEY

TSCA = Toxic Substances Control Act  
 WHMIS = Workplace Hazardous Materials Information System (Canada)  
 IARC = International Agency for Research on Cancer

DSL = Domestic Substances List (Canada)  
 CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act

## SECTION 16 OTHER INFORMATION

|                           |  |
|---------------------------|--|
| <b>Preparation Date</b>   | January 2020   |
| <b>Revision Date</b>      | April 2022   |
| <b>Summary of Changes</b> | Branding update  |
| <b>Disclaimer</b>         | <p>The information and recommendations contained herein are to the best of Performance Roof Systems' knowledge and belief, accurate and reliable as of the date issued. Performance Roof Systems does not warrant or guarantee their accuracy or reliability, and Performance Roof Systems shall not be liable for any loss or damage arising out of the use thereof.</p> <p>The information and recommendations are offered for the users consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the users responsibility to make certain that it is relying upon the most recent, updated, information and recommendations available from Performance Roof Systems.</p> |