


SENTINEL[®] PVC MOLDED CORNERS



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PD10174-Rev. 220412

DESCRIPTION:

SENTINEL PVC Molded Corners are injection molded, unreinforced flashings that are installed to flash 90-degree inside and outside corners. SENTINEL PVC Molded inside and outside corners are white in color.

STORAGE:

All materials must be stored in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and application.

APPLICATION:

SENTINEL PVC Molded Corners are installed via heat welding. Heat weld each seam using a hot-air welder. Refer to SOPREMA's specifications and installation instructions for additional application guidelines.

USES:

SENTINEL PVC Molded Corners are pre-molded and are used for flashing the inside and outside corners on a variety of details. Installation is fast and easy with no cutting or stretching required.

QUICK FACTS

WIDTH (in)	LENGTH (in)	HEIGHT (in)	THICKNESS (mils)
6 (15.2 cm)	6 (15.2 cm)	6 (15.2 m)	85 (2.2 mm)

PACKAGING

SKU #	PRODUCT	DESCRIPTION	PACKAGING
P501	Prefabricated outside corners	For use with white membranes	20 per carton
P502	Prefabricated inside corners	For use with white membranes	20 per carton