

# SENTINEL<sup>®</sup> PVC PIPE FLASHINGS



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PD10176-Rev. 220331

## DESCRIPTION:

**SENTINEL PVC Pipe Flashings** are manufactured from fiberglass reinforced PVC membrane and feature a split design to fit around protrusions up to 6 inches (15.2 cm) in diameter.

## STORAGE:

All materials must be stored in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and application.

## APPLICATION:

**SENTINEL PVC Pipe Flashings** are hot-air welded to the field membrane. Seal the top of the pipe flashing watertight with mastic and a pipe clamp (included). Refer to SOPREMA's specifications and installation instructions for additional application guidelines.

### QUICK FACTS

DIAMETER (in)	HEIGHT (in)	THICKNESS (mils)
1-6 (2.5 to 15.2 cm)	8 (20 cm)	60 (1.5 mm)

## PACKAGING

SKU #	PRODUCT	DESCRIPTION	PACKAGING
P601	SENTINEL PVC Pipe Flashing - 1 in (2.5 cm)	Fits pipes up to 1 in diameter	8 per carton
P602	SENTINEL PVC Pipe Flashing - 2 in (5.1 cm)	Fits pipes 1 in to 2 in diameter	8 per carton
P603	SENTINEL PVC Pipe Flashing - 3 in (7.6 cm)	Fits pipes 2 in to 3 in diameter	8 per carton
P604	SENTINEL PVC Pipe Flashing - 4 in (10.2 cm)	Fits pipes 3 in to 4 in diameter	8 per carton
P605	SENTINEL PVC Pipe Flashing - 5 in (12.7 cm)	Fits pipes 4 in to 5 in diameter	8 per carton
P606	SENTINEL PVC Pipe Flashing - 6 in (15.2 cm)	Fits pipes 5 in to 6 in diameter	8 per carton

