


SOPRASEAL[®] MESH

Reinforced Non-Woven Polyester Fabric



APPLICATIONS

WALLS

PRODUCT DATA SHEET PD10296 - REV.220630

PRODUCT NUMBERS:

- A502 - **SOPRASEAL MESH** (4" x 180')
- 22239 - **SOPRASEAL MESH** (6" x 180')
- 22240 - **SOPRASEAL MESH** (9" x 180')

DESCRIPTION & FEATURES:

SOPRASEAL MESH is a reinforced non-woven polyester fabric. It is used for above-grade applications with **SOPRASEAL LM 202 VP** or **SOPRASEAL LM 203**.

SOPRASEAL MESH reinforces **SOPRASEAL LM 202 VP** or **SOPRASEAL LM 203** over acceptable rough openings, sheathing joints, and transitions.

PACKAGING:

SPECIFICATION	SOPRASEAL MESH
Dimensions	A502: 4 in (100 mm) x 180 ft (55 m) 22239: 6 in (150 mm) x 180 ft (55 m) 22240: 9 in (230 mm) x 180 ft (55 m)
Weight	2.45 oz/y ² (83 g/m ²)

All values are nominal

LIMITATIONS:

Protect **SOPRASEAL MESH** during transportation and installation to avoid physical damage.

For complete information on product installation, please consult your SOPREMA representative.

APPLICATION:



GLOVED HANDS

Apply **SOPRASEAL LM 202 VP** or **SOPRASEAL LM 203** to all sheathing joints, terminations, inside and outside corners, and rough openings.

Immediately place and center **SOPRASEAL MESH** over wet **SOPRASEAL LM 202 VP** or **SOPRASEAL LM 203**, embedding and completely saturating **SOPRASEAL MESH**.

Ensure **SOPRASEAL MESH** extends evenly on both sides of the sheathing joint. Lap a minimum of 2 1/2" (64 mm) of **SOPRASEAL MESH** at intersections.

When product is applied with a roller, allow to dry to touch, before applying **SOPRASEAL LM 202 VP** or **SOPRASEAL LM 203** to entire wall surface. When product is spray applied, "wet on wet" application is acceptable.

STORAGE:

Store **SOPRASEAL MESH** in a cool, dry place, and protect it from moisture.