

# ALSAN® COATING SIL 402

## ROOF COATING



ALSAN Coating SIL 402 is a VOC compliant, high solids, single component, silicone roof coating and protective barrier for various low-slope roof surfaces and substrates. Upon cure, ALSAN Coating SIL 402 forms a durable, weatherproof coating that is highly resistant to degradation from UV and natural weathering. ALSAN Coating SIL 402 may be applied as a maintenance coating over sound, dry and aged single-ply (TPO, PVC, EPDM and CSPE), modified bitumen, BUR, metal roofing and/or other approved existing coatings.

### RELATED PRODUCTS



**ALSAN® SIL 402 FLASHING**  
ALSAN SIL 402 Flashing is a silicone mastic used to prepare seams, penetrations & fasteners for coating.






**ALSAN® BLEED BLOCKING PRIMER**  
ALSAN Bleed Blocking Primer is an acrylic primer/basecoat used to enhance adhesion and stop asphalt bleed through.



**ALSAN® COATING SIL 402 WALKWAY GRADE**  
ALSAN Coating SIL 402 Walkway Grade is a silicone coating that is tinted to safety yellow and is designed for high traffic areas and safety lines on roofing projects.

- Durable and great ponding water resistance
- Resistant to UV and natural weathering
- Compatible with a wide variety of substrates

### QUICK FACTS

PACKAGING	5-gal. bucket, 55-gal. drum		
NEXT COAT	<8 Hours @ 75°F (24°C) @ 50% RH		
FULLY CURED	>8 hours @ 75°F (24°C) @ 50% RH		
APPLICATION			
	ROLLER	BRUSH	SPRAY

