

COLPLY® ADHESIVE

SBS-Modified Bitumen Membrane Adhesive

PRODUCT DATA SHEET PD10090 - REV 230323



APPLICATIONS

ROOFING

PRODUCT NUMBERS:

- A230 - 5 Gal (18.9 L) Pail
- A232 - 55 Gal (208.1 L) Drum
- A233 - 350 Gal (1,324.8 L) Tote

DESCRIPTION & FEATURES:

COLPLY ADHESIVE is a high quality, single component, asphalt cutback adhesive formulated specifically for adhering SBS-modified bitumen membrane systems.

COLPLY ADHESIVE is blended with specially selected and processed asphalt and performance additives that contribute to its smooth troweling consistency.

- Excellent elongation and recovery properties accommodate for thermal movement
- Meets the requirements of ASTM D3019 Type III
- VOC compliant — meets stringent EPA air quality standards with low fumes

APPLICATION:



NOTCHED
TROWEL



V-NOTCHED
SQUEEGEE



SPRAYER

COLPLY ADHESIVE is applied to approved substrates using a trowel, v-notched squeegee or sprayer. Apply **COLPLY ADHESIVE** at a rate of 1.5 to 2.5 gal per square over smooth surfaces. The application rate over irregular/porous surfaces will vary, adjust rates to ensure full coverage.

Refer to the SOPREMA SBS-Modified Bitumen Membrane Roofing Technical Manual for additional application guidelines.

STORAGE:

Store the container in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Storage temperature range should be between 55°F (12.8°C) and 80°F (26.7°C). Approximate shelf life is 12 months from the date of manufacture when properly stored and sealed.

LIMITATIONS

When the ambient temperature is below 40°F (4.4°C), material should be warmed to a temperature of 70°F (21°C) at the time of application. Conditioning may take up to 24 hours to ensure chemical has reached optimal application temperature.

TESTING & APPROVALS:



MIAMI-DADE COUNTY
APPROVED

NOA # 20-0825.11


WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

COLPLY® ADHESIVE

SBS-Modified Bitumen Membrane Adhesive

PRODUCT DATA SHEET PD10090 - REV 230323



APPLICATIONS

ROOFING

TECHNICAL INFORMATION & TESTING:

PHYSICAL PROPERTIES		
PROPERTY	VALUE	ASTM TEST METHOD
Technology	Polymer-modified asphaltic base	-
Color	Black	-
Density, lb/gal	9.0 - 10.0	D2240
Coverage, gal/100 ft²	1.5 - 2.5	-
Flash point, °F (°C)	105 (40.6)	D92
Non-volatile contents (total solids), %	78 - 83	D6511
Application temperature, °F (°C)	40-120 (4.4 - 21)	-
Storage temperature, °F (°C)	55 - 80 (12.8 - 26.7)	-
Cleanup	Mineral spirits	-
Shelf life, months	12	-
VOC content, g/L	< 250	D2369

* Data is represented by average values, unless noted otherwise.