

SOPRANATURE[®] MRB 30

Moisture Retention/Drainage Board



APPLICATIONS

VEGETATED

PRODUCT DATA SHEET PDS220614 - REV 230712

PRODUCT NUMBERS:

- 27110 - 3.3 x 4 ft (1 x 1.2 m) - Board

DESCRIPTION & FEATURES:

SOPRANATURE MRB 30 is a moisture retention board with drainage properties made from 100% recycled polyester. **SOPRANATURE MRB 30** is used in flat or sloped green roofing systems to retain a certain amount of water and channel excess to the water outlets. It can also be used on any roof or plaza-deck that needs water management or serve as a protection board over the waterproofing membranes.

APPLICATION:

Install **SOPRANATURE MRB 30** boards side by side directly on the surface making sure to leave no gaps between the boards.

Refer to SOPREMA's published technical literature for additional details and application requirements.

STORAGE:

Store boards flat on the original pallet and maintain in a horizontal position to prevent damage, creases and wrinkles in the board during storage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.

SUSTAINABILITY



RECYCLED CONTENT
POST-CONSUMER

100 %

SOPRANATURE[®] MRB 30

Moisture Retention/Drainage Board



APPLICATIONS

VEGETATED

PRODUCT DATA SHEET PDS220614 - REV 230712

TECHNICAL INFORMATION & TESTING:

SHEET PROPERTIES	
PROPERTY	VALUE
Material	100% recycled polyester
Color	Dark gray

DIMENSIONS & MASS	
PROPERTY	VALUE
Length , ft (m)	3.3 (1)
Width , in (m)	4.0 (1.2)
Coverage ,* ft ² (m ²)	12.9 (1.2)
Weight , lb (kg)	5.2 (2.4)
Boards per pallet	70
Thickness , in (mm)	1.18 (30)

PHYSICAL PROPERTIES		
PROPERTY	VALUE	ASTM TEST METHOD
Compressive strength 10% deformation , psi (kPa)	0.42 (2.9)	D1621
Dry weight , lb/ft (kg/m ²)	0.6 (3.0)	E2397
Fully saturated water retention , lb/ft (kg/m ²)	4.4 (21.6)	E2397
Puncture resistance , lbf (N)	49.5 (220)	D4833
Flow rate @ 20 kPa, Hydraulic gradient of 1.0 , gal/min/ft (L/min/m)	0.017 (0.21)	D4716

Data is represented by average values, unless noted otherwise.