

SENTINEL® KEE T-JOINT PATCHES

Prefabricated KEE T-Joint Membrane



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10450 - REV 230504

PRODUCT NUMBERS:

- P626 - 4.5 in DIA (11.4 cm) - Rounds (White)

DESCRIPTION & FEATURES:

SENTINEL KEE T-JOINT PATCHES are made using 60 mil, reinforced SENTINEL KEE P150 membrane cut into a perfect 4.5 in-diameter circle. **SENTINEL KEE T-JOINT PATCHES** are designed to seal seam laps where perimeter and/or header sheets intersect (T-Joint) in SENTINEL PVC systems.

- Provides a more professional and uniform appearance compared to field-fabricated covers
- Offers significant labor savings compared to hand cut flashings

APPLICATION:



HOT-AIR
WELDING

SENTINEL KEE T-JOINT PATCHES shall be hot-air welded to the membrane at all t-joint intersections. Chamfer the welding seam prior to installing **SENTINEL KEE T-JOINT PATCHES**, using an edging tool or by heating the edge and rolling.

Refer to the SOPREMA PVC Membrane Roofing Technical Manual for complete application guidelines.

PACKAGING & DIMENSIONS:

| PROPERTY | VALUE |
|-----------------------------------|------------|
| Size (diameter) , in (cm) | 4.5 (11.4) |
| Packaging | 100/box |
| Weight (per box) , lb (kg) | 3.5 (1.6) |
| Thickness , mils (mm) | 60 (1.5) |

STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

LIMITATIONS:

If membrane has been exposed to the weather, clean area with approved PVC membrane cleaner prior to installation. Refer to the SOPREMA PVC Membrane Roofing Technical Manual for recommendations.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.