SOPRANATURE® PAVER PEDESTAL

Paver Pedestal and Accessories

PRODUCT DATA SHEET PDS10460 - REV 231106



PRODUCT NUMBERS:

For ordering information contact customer service.

DESCRIPTION & FEATURES:

SOPRANATURE PAVER PEDESTALS support paving blocks on pedestrian traffic terraces. Manufactured from injection molded polypropylene, SOPRANATURE PAVER PEDESTALS consist of a head screw nut assembly with an 8 in (200 mm) wide base plate. SOPRANATURE PAVER PEDESTALS allow for the adjustment and the leveling of paving blocks and are available in 6 references for heights from 1 to 10.2 inches (25 to 260 mm).

- Available in varying heights to suit a variety of applications
- Fast and easy installation promotes labor savings
- · Screw-to-adjust pedestals ensure perfectly level decks
- · Impervious to water, mold and freeze/thaw cycles

APPLICATION:

SOPRANATURE PAVER PEDESTALS can be installed on any base designed to support the load of the entire pedestal system. Since the installation of a plaza deck requires additional structural resistance in an existing building, SOPREMA recommends an in-depth analysis of its capacities by a building structural engineer.

Pedestals are packaged with the top and base fully assembled in the pedestal's lowest height position. To increase the height, simply hook the key on the screw nut in the center of the paver pedestals, turn the key clockwise to lower the threaded screw on the support and turn counterclockwise to raise it. DO NOT extend the height of the pedestal past the built-in thread engagement indicators unless adding an EXTENSION.

At the corners or on the edges of the terraces, the head spacers should be leveled using a cutter, cutting pliers or a hacksaw.

> Refer to SOPREMA's published technical literature for additional details and application requirements.

STORAGE:

Store boxes in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.



SOPRANATURE® PAVER PEDESTAL

Paver Pedestal and Accessories

PRODUCT DATA SHEET PDS10460 - REV 231106





APPLICATIONS

VEGETATED

TECHNICAL INFORMATION & TESTING:

PRODUCT SPECIFICATIONS				
PROPERTY		VALUE		STANDARDS
Material		Injection molded polypropylene		-
Breaking strength, over the entire surface, lbf (Kn)		> 2,248.1 (>10)		CSTB DTU 43-1
Breaking strength, over one quarter of the surface, lbf (Kn)		> 1,124 (>5)		CSTB DTU 43-1
PEDESTAL MODEL HEIGHT		PEDESTALS QTY/BOX		QTY/PALLET
H8/20	5/16 - 3/4 in (8 - 20 mm)		30	100
H25/40	1 - 11/2 in (25 - 40 mm)		88	30
H40/60	1 1/2 - 2 5/8 in (40- 67 mm)		120	12
H60/90	2 3/8 - 3 1/2 in (60- 90 mm)		60	20
H90/150	3 1/2 - 5 7/8 in (90- 150 mm)		60	12
H150/260	5 7/8 - 10 1/4 in (150 - 260 mm)		48	12



SOPRANATURE® PAVER PEDESTAL

Paver Pedestal and Accessories

PRODUCT DATA SHEET PDS10460 - REV 230322

o prem



VEGETATED

ACCESSORIES



