


- NOTES:
1. SOPREMA DETAIL DRAWINGS: REFER TO SOPREMA AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY SOPREMA FOR THE SOLE PURPOSE OF ISSUING A SOPREMA WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.
  2. HOT WORK: THE CONTRACTOR IS RESPONSIBLE FOR DETERMINING APPROPRIATE CONDITIONS TO UTILIZE HEAT-WELDING EQUIPMENT. REFER TO LOCAL CODES AND BUILDING OWNER'S REQUIREMENTS FOR HOT WORK OPERATIONS.
  3. PRIMER: WHERE NOT SHOWN OR INDICATED ON DETAIL DRAWINGS, REFER TO MATERIAL PRODUCT DATA SHEETS FOR PRIMER APPLICATION REQUIREMENTS
  4. FLASHING PLIES MUST EXTEND VERTICALLY A MINIMUM OF 8" FROM ROOF SURFACE. FLASHING PLIES EXTENDING VERTICALLY MORE THAN 60" FROM ROOF SURFACE MUST BE ADHERED AND MECHANICALLY FASTENED ALONG THE TOP LEADING EDGE. REFER TO PUBLISHED DOCUMENTATION.

|  |   |                  |  |  |       |
|--|---|------------------|--|--|-------|
| <br><br>US CORPORATE ADDRESS<br>310 QUADRAL DRIVE<br>WADSWORTH, OHIO 44281<br><a href="http://www.soprema.us">www.soprema.us</a><br>Tel: 330.334.0066 | PROJECT:  |                  | DRAWN BY: SOPREMA TECHNICAL SUPPORT, GGALLOWAY |  |       |
|  | TITLE:<br><br>KEE MEMBRANE, INSULATED<br><br>CURB WITH REMOVABLE<br><br>COUNTERFLASHING | NO.:             | REVISION:                                      |  | DATE: |
|  |   |                  |  |  |       |
|  |   | DATE: 10.12.2023 | DRAWING NUMBER:<br><b>US.RKEE.05.03</b>        |  |       |
|  |   | SCALE: NTS       |  |  |       |