

# SENTINEL® KEE BOOT FLASHING

Pre-Fabricated KEE Conical Pipe Flashing



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10447 - REV 240108

## PRODUCT NUMBERS:

- P620 - 1 - 6 in (2.5 - 15.2 cm) DIA - Split (White)
- P621 - 1 - 6 in (2.5 - 15.2 cm) DIA - Closed (White)
- P622 - 6 - 12 in (15.2 - 30.5 cm) DIA - Split (White)
- P623 - 6 - 12 in (15.2 - 30.5 cm) DIA - Closed (White)

## DESCRIPTION & FEATURES:

**SENTINEL KEE BOOT FLASHINGS** are factory fabricated, cone-shaped boots made using reinforced SENTINEL KEE P150 membrane. Available for traditional or split-pipe applications, **SENTINEL KEE BOOT FLASHINGS** are offered in two sizes to fit either a 1 - 6 in or 6 -12 in pipe diameters. Each pipe flashing is shipped with a stainless steel clamping ring. **SENTINEL KEE BOOT FLASHINGS** are available in white.

- Prefabricated flashings not only enhance a roof's aesthetics but add lasting durability to a roof system's long-term performance
- Eliminating the need to customize flashings on site contributes to cleaner installations with less job-site waste
- Prefabricated accessories are fast and easy to install, providing greater job site productivity and reduced labor costs

## APPLICATION:



HOT-AIR  
WELDING

**SENTINEL KEE BOOT FLASHINGS** are hot-air welded to the field membrane. Seal the top of the pipe flashing watertight with mastic and a pipe clamp (included).

Contact SOPREMA or refer to published guidelines for additional details and application requirements.

## PACKAGING & DIMENSIONS:

PROPERTY	VALUE	
<b>Size (diameter), in (cm)</b>	1-6 (2.5 -15.2)	6-12 (15.2 - 30.5)
<b>Packaging</b>	10/box	
<b>Thickness, mils (mm)</b>	60 (1.5)	

## STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

## WARRANTY:

For more information refer to [www.SOPREMA.us](http://www.SOPREMA.us) or contact your SOPREMA representative.

