

SENTINEL® KEE T-JOINT PATCHES

Prefabricated KEE T-Joint Membrane



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PDS10450 - REV 240108

PRODUCT NUMBERS:

- P626 - 4.5 in DIA (11.4 cm) - Rounds (White)

DESCRIPTION & FEATURES:

SENTINEL KEE T-JOINT PATCHES are made using 60 mil, reinforced SENTINEL KEE P150 membrane cut into a perfect 4.5 in-diameter circle. **SENTINEL KEE T-JOINT PATCHES** are designed to seal seam laps where perimeter and/or header sheets intersect (T-Joint) in SENTINEL PVC systems.

- Provides a more professional and uniform appearance compared to field-fabricated covers
- Offers significant labor savings compared to hand cut flashings

APPLICATION:



HOT-AIR
WELDING

SENTINEL KEE T-JOINT PATCHES shall be hot-air welded to the membrane at all t-joint intersections. Chamfer the welding seam prior to installing **SENTINEL KEE T-JOINT PATCHES**, using an edging tool or by heating the edge and rolling.

Contact SOPREMA or refer to published guidelines for additional details and application requirements.

PACKAGING & DIMENSIONS:

PROPERTY	VALUE
Size (diameter) , in (cm)	4.5 (11.4)
Packaging	100/box
Thickness , mils (mm)	60 (1.5)

STORAGE:

Store boxes in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture.

WARRANTY:

For more information refer to www.SOPREMA.us or contact your SOPREMA representative.