

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ALSAN CIVIL P70

1.2. Relevant identified uses of the substance or mixture and uses advised against

Fast curing polymethyl methacrylate primer

1.3. Details of the supplier of the safety data sheet

SOPREMA INC
310 Quadral Drive
Wadsworth, OH 44281 - USA
Tel: 800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) VR2 4H3
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport, MS 39507
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (acct # CCN20515); 24/7, 1 (613) 996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS US)

Flam. Liq. 2	H225
Acute Tox. 4 (Oral)	H302
Skin Irrit. 2	H315
Skin Sens. 1	H317
Repr. 2	H361
STOT SE 3	H335

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS02



GHS07



GHS08

Signal word (GHS US) : Danger

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US)	: H225 - Highly flammable liquid and vapor H302 - Harmful if swallowed H315 - Causes skin irritation H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation H361 - Suspected of damaging fertility or the unborn child
Precautionary statements (GHS US)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection. P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell. P302+P352 - If on skin: Wash with plenty of water. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P308+P313 - If exposed or concerned: Get medical advice/attention. P312 - Call a poison center or doctor if you feel unwell. P330 - Rinse mouth. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P363 - Wash contaminated clothing before reuse. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Methyl methacrylate	(CAS-No.) 80-62-6	30 – 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis-	(CAS-No.) 38668-48-3	1 – 5	Acute Tox. 2 (Oral), H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
Toluene	(CAS-No.) 108-88-3	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2-Hydroxyethyl acrylate	(CAS-No.) 818-61-1	0.1 – 1	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400

SECTION 4: First Aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention/advice.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention if pain, blinking or redness persists. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of damaging fertility. Suspected of damaging the unborn child.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : May cause skin irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : May cause eye irritation.
- Symptoms/effects after ingestion : Harmful if swallowed.
- Chronic symptoms : May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Dry powder. Water spray.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : Substance is not explosive. The product may still produce explosive vapor/air mixtures.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Precautionary measures fire : Eliminate all ignition sources if safe to do so.
- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.
- Other information : Vapors may travel long distances along ground before igniting/flashing back to vapor source. This material is flammable and may be ignited by heat, sparks, or static electricity.

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. Eliminate all ignition sources if safe to do so. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.
Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Provide good ventilation in process area to prevent formation of vapor. Ground/bond container and receiving equipment. Prohibit smoking in storage area. Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container closed when not in use. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a dry, cool and well-ventilated place. Prohibit smoking in storage area.
Incompatible materials : No data available.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl methacrylate (80-62-6)		
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL [ppm]	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2022

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl methacrylate (80-62-6)		
OSHA	OSHA PEL TWA [1]	410 mg/m ³
OSHA	OSHA PEL TWA [2]	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	1000 ppm
NIOSH	NIOSH REL TWA	410 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
Paraffin waxes and Hydrocarbon waxes (8002-74-2)		
ACGIH	ACGIH OEL TWA	2 mg/m ³ (fume)
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; nausea
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL TWA [1]	2 mg/m ³ Vacated
NIOSH	NIOSH REL TWA	2 mg/m ³ (fume)
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Toluene (108-88-3)		
ACGIH	ACGIH OEL TWA [ppm]	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL TWA [2]	200 ppm
OSHA	OSHA PEL C [ppm]	300 ppm (500 ppm Peak [10 minutes])
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
IDLH	IDLH [ppm]	500 ppm
NIOSH	NIOSH REL TWA	375 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
NIOSH	NIOSH REL STEL	560 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	150 ppm
2-Hydroxyethyl acrylate (818-61-1)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing.

Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.
Eye protection	: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
Respiratory protection	: Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Color	: Clear
Odor	: Strong solvent
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 10 °C (50 °F) closed cup (value for methyl methacrylate)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: > 1
Relative density	: No data available
Density	: 1.02
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 435 °C (815°F)
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: ≈ 1200 cP
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: < 5 g/L
-------------	-----------

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Formation of flammable gases/vapors.

10.4. Conditions to avoid

Store away from heat and light. High temperatures.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Methyl methacrylate (80-62-6)	
LD50 oral rat	7872 mg/kg
LD50 dermal rabbit	> 5 g/kg
LC50 Inhalation - Rat	29.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4632 ppm/4h

Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 oral rat	> 5000 mg/kg (SOURCE: CHEMVIEW)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 3600 mg/kg

2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
LD50 oral rat	> 25 mg/kg (range >25 - <200 mg/kg; source: ECHA)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Toluene (108-88-3)	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 Inhalation - Rat	384 mg/m ³

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : Not applicable

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects	: Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of damaging fertility. Suspected of damaging the unborn child.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.
Chronic symptoms	: May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without a permit.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)	: UN1263 Paint, 3, II
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Transport by sea (IMDG)

Transport document description (IMDG)	: UN 1263 PAINT, 3, II
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 5 L

Air transport (IATA)

Transport document description (IATA)	: UN 1263 Paint, 3, II
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

ALSAN CIVIL P70 PRIMER

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Reproductive toxicity Health hazard - Acute toxicity (any route of exposure) Physical hazard - Flammable (gases, aerosols, liquids, or solids)
-------------------------------------	---

Methyl methacrylate (80-62-6)

CERCLA RQ	1000 lb
-----------	---------

Toluene (108-88-3)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Toluene (108-88-3)		X				7000 µg/day

ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Methyl methacrylate (80-62-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Toluene (108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Silica, amorphous (7631-86-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
2-Hydroxyethyl acrylate (818-61-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Full text of H-statements	
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapor.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.


ALSAN CIVIL P70 PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.



Indication of changes:

Revision 1.0: New SDS Created.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.