

# ALSAN® CIVIL 755

## WATERPROOFING



ALSAN CIVIL 755 is a three-component polymethyl methacrylate-based (PMMA) waterproofing sprayable liquid membrane. ALSAN CIVIL 755 is utilized as an unreinforced waterproofing system for bridges, parking decks and various other civil engineering structures.

- Rapid curing and easy application provides same-day installation
- Can be applied in temperatures as low as -13°F
- Seamless, monolithic waterproofing membrane
- Available in grey or blue

### RELATED PRODUCTS




**ALSAN CIVIL P70**  
A two-component translucent primer used to improve the adhesion of ALSAN CIVIL systems and ANTIROCK membranes on concrete and steel substrates.



**ALSAN RS CATALYST POWDER**  
ALSAN RS Catalyst Powder is a reactive agent used to induce curing of ALSAN CIVIL products.

### QUICK FACTS

PACKAGING	18-20 kg pails or 180-200 kg drums
APPLICATION TEMPERATURE	-13 to 95°F (-25 to 35°C)
POT LIFE	12 Minutes @ 68°F (20°C)
RAINPROOF	20 Minutes @ 68°F (20°C)
FULLY CURED	1 Hour @ 68°F (20°C)
APPLICATION	 SPRAY